
reset == 0 | prst_n == 0
cdu_diu_rreq = 0
ignore_data = 0
cdu_diu_rreq = 1
Reset
go == 1 &
done_band == 0
cdu_diu_rreq = 0
ignore_data = 0
go == 0
cdu_diu_rreq = 1
ignore_data = 0
Idle

FIG. 1


receive document
page layouts and objects
memory buffer
rasterize page description
compress page image
Host PC
USB or indirect (via ISIMaster) connection
memory buffer
compressed multi-layer page images
expand page image
dither contone layer
composite black layer over dithered contone
render Netpage infrared tags to IR layer
print page
SoPEC Device
Bi-lithic Printhead

FIG. 2


replaceable
ink cartridge
ink cartridge
QA chip
Printer
QA chip
ink
USB from Host
SoPEC
Device #0
A4 Bi-lithic
printhead
printhead assembly
high speed
low spe d

FIG. 3


high speed
low speed
replaceable ink cartridge
ink cartridge QA chip
A4 Bi-lithic printhead
A4 Bi-lithic printhead
SoPEC Device #0
ISI
SoPEC Device #1
Printer QA chip
Printer QA chip
printhead assembly
USB from Host

FIG. 4


high speed
low speed
replaceable ink cartridge
ink cartridge QA chip
ink
A3 Bi-lithic printhead
Printer QA chip
SoPEC Device #0
ISI
SoPEC Device #1
Printer QA chip
printhead assembly
USB from Host

FIG. 5


high speed
low speed
replaceable ink cartridge
ink cartridge QA chip
replaceable ink cartridge
ink cartridge QA chip
Printer QA chip
SoPEC Device #2
Printer QA chip
SoPEC Device #3
A3 Bi-lithic printhead
A3 Bi-lithic printhead
ISI
Printer QA chip
SoPEC Device #0
SoPEC Device #1
Printer QA chip
printhead assembly
USB fr m H st

FIG. 6


high speed
low speed
replaceable ink cartridge
ink cartridge QA chip
A4 Bi-lithic printhead
SoPEC used as DRAM storage
Printer QA chip
SoPEC Device #0
ISI
SoPEC Device #1
printhead assembly
USB from Host

FIG. 7


high speed
low speed
Printer QA chip
SoPEC Device #2
SoPEC Device #3
Printer QA chip
A3 Memjet printhead
ink
ISI
replaceable ink cartridge
ink cartridge QA chip
A3 Memjet printhead
Printer QA chip
SoPEC Device #0
SoPEC Device #1
Printer QA chip
DRAM
ISI port 0
ISI port 1
Bridge Chip
printhead assembly
C nnecti n
t H st

FIG. 8


blank page
page header
single band page
page header
band 0
2 band page
page header
band 0
band 1
multi band page
page header
band 0
band 1
...
band n

FIG. 9


band header
bi-level plane
contone plane
tag data plane
band n
band n

FIG. 10


CPU
processed to become
SoPEC's DRAM
page/band header
bi-level plane
contone interleaved plane
tag data plane
register commands
...
SoPEC's Registers
...
SCB
passed through
passed through
passed through
passed through
Host RIP
page/band header
bi-level plane
contone interleaved plane
tag data plane
compressed page

FIG. 11


target top margin
target page
printable page area
(physical page)
target left margin
target right margin
target bottom margin

FIG. 12


CPU sub-system
DRAM sub-system
eDRAM
DIU
DRAM bus
CPU
RDU
MMU
Master
Slave
Print Engine Pipeline sub-system
CDU
CFU
LBD
SFU
TE
TFU
HCU
DNC
DWU
LLU
PHI
Bi-lithic Printhead
TIM
Boot ROM
ICU
PSS
SCB
USB Host
USB PHY
USB Device
ISI
DMA Crtl
Bus CPU Subsystem
CPR
GPIO
Motor Control, LSS, ISI, LED, etc.
LSS Master
PCU
PEP Configuration Bus

FIG. 13


0xFFFF_FFFF
0x4028_0000
DRAM Regions
0x4000_0000
0x0002_C000
0x0002_0000
0x0001_0000
0x0000_0000
Unused
DRAM
Unused
PCU Mapped Registers
Peripheral Registers
ROM
Accesses in this area are not allowed and result in a bus error exception.
Accesses in this area are via the DIU bus and are controlled by permissions set in the MMU.
Accesses in this area are not allowed and result in a bus error exception.
Accesses in this area are via the CPU bus and are controlled by permissions set in each peripheral.

FIG. 14


AHB Controller
AHB Interface
LEON CPU and Caches
MMU
Address Decoder
Realtime Debug Unit
cpu_adr[21:2]
cpu_dataout[31:0]
dram_cpu_data[255:0]
cpu_diu_rreq
diu_cpu_rack
diu_cpu_rvalid
cpu_diu_wdatavalid
diu_cpu_write_rdy
cpu_diu_wadr[21:4]
cpu_diu_wdata[127:0]
cpu_diu_wmask[15:0]
cpu_acode[1:0]
cpu_rwn
cpu_cpr_sel
cpr_cpu_rdy
cpr_cpu_data[31:0]
cpu_gpio_sel
gpio_cpu_rdy
gpio_cpu_data[31:0]
cpu_icu_sel
icu_cpu_rdy
icu_cpu_data[31:0]
cpu_lss_sel
lss_cpu_rdy
lss_cpu_data[31:0]
cpu_pcu_sel
pcu_cpu_rdy
pcu_cpu_data[31:0]
cpu_scb_sel
scb_cpu_rdy
scb_cpu_data[31:0]
cpu_tim_sel
tim_cpu_rdy
tim_cpu_data[31:0]
cpu_rom_sel
rom_cpu_rdy
rom_cpu_data[31:0]
cpu_pss_sel
pss_cpu_rdy
pss_cpu_data[31:0]
cpu_diu_sel
diu_cpu_rdy
diu_cpu_data[31:0]
diu_cpu_berr
pss_cpu_berr
rom_cpu_berr
tim_cpu_berr
scb_cpu_berr
pcu_cpu_berr
lss_cpu_berr
icu_cpu_berr
gpio_cpu_berr
cpr_cpu_berr
diu_cpu_debug_valid
tim_cpu_debug_valid
scb_cpu_debug_valid
pcu_cpu_debug_valid
lss_cpu_debug_valid
icu_cpu_debug_valid
gpio_cpu_debug_valid
cpr_cpu_debug_valid
debug_data_out[31:0]
debug_data_valid
debug_cntrl[32:0]
prst_n
pclk
icu_cpu_ilevel[3:0]
cpu_iack
cpu_icu_ilevel[3:0]

FIG. 15


pclk
cpu_adr[21:2]
LSS address
PEP address
Supervisor stack
cpu_rwn
cpu_acode[1:0]
Supvr Data
User Data
Supvr Data
cpu_lss_sel
lss_cpu_rdy
lss_cpu_berr
cpu_dataout[31:0]
LSS data
cpu_pcu_sel
pcu_cpu_berr
pcu_cpu_rdy
pcu_cpu_data[31:0]
0x0000_0000

FIG. 16


prst_n == 0
block_cpu_rdy = 0
block_cpu_berr = 0
block_cpu_data = debug_reg_data
block_cpu_debug_valid = 1
cpu_block_sel == 0
block_cpu_data = reg_data
block_cpu_debug_valid = 1
idle
cpu_block_sel == 1
AND cpu_rwn == 1
AND valid_access == 1
AND reg_available == 1
block_cpu_rdy = 1
block_cpu_berr = 0
block_cpu_data = reg_data
block_cpu_debug_valid = 0
Read Access Complete
block_cpu_rdy = 0
block_cpu_debug_valid =1
block_cpu_data = debug_reg_data
cpu_block_sel == 1
AND cpu_rwn == 0
AND valid_access == 1
AND reg_available == 1
block_cpu_rdy = 1
block_cpu_berr = 0
reg_data = cpu_dataout
Write Access Complete
block_cpu_rdy = 0
cpu_block_sel == 1
AND valid_access == 1
AND reg_available == 0
block_cpu_rdy = 0
block_cpu_berr = 1
cpu_block_sel == 1
AND valid_access == 0
block_cpu_rdy = 0
block_cpu_berr = 1
block_cpu_data = 0x00000000
Invalid Read Access
block_cpu_berr = 0
cpu_block_sel == 1
AND valid_access == 1
AND reg_available == 0
block_cpu_rdy = 0
block_cpu_berr = 0
Wait
reg_available == 1
AND cpu_rwn == 0
block_cpu_rdy = 1
reg_data = cpu_dataout
reg_available == 1
AND cpu_rwn == 1
block_cpu_rdy = 1
block_cpu_data = reg_data
reg_available == 0
cpu_block_sel == 1
AND cpu_rwn == 0
AND valid_access == 1
block_cpu_rdy = 0
block_cpu_berr = 1
Invalid Write Access
block_cpu_berr = 0

FIG. 17


0xFFFF_FFFF
0x4028_0000
DRAM Regions
0x4000_0000
0x0002_C000
0x0002_0000
0x0001_0000
0x0000_0000
Unused
DRAM
Unused
PCU Mapped Registers
Peripheral Registers
ROM
Accesses in this area are not allowed and result in a bus error exception.
Accesses in this area are via the DIU bus and are controlled by permissions set in the MMU.
Accesses in this area are not allowed and result in a bus error exception.
Accesses in this area are via the CPU bus and are controlled by permissions set in each peripheral.

FIG. 18


haddr[31:0]
hwdata[31:0]
hrdata[31:0]
hsel
hwrite
htrans[1:0]
hsize[2:0]
hburst[2:0]
hprot[3:0]
hmaster[3:0]
hmasterlock
hready
hresp[1:0]
hsplit[15:0]
LEON AHB Bridge
MMU Control Block
CPU Subsystem Bus Interface
RDU
debug_data_out
debug_data_valid
debug_cntrl
dram_cpu_data[255:0]
cpu_diu_wdata[127:0]
cpu_diu_rreq
cpu_diu_wreq
cpu_diu_wdatavalid
diu_cpu_rack
diu_cpu_rvalid
diu_cpu_write_rdy
cpu_diu_wadr[21:4]
cpu_diu_wmask[15:0]
icu_cpu_ilevel[3:0]
cpu_iack
cpu_icu_ilevel[3:0]
cpu_rwn
cpu_dataout[31:0]
cpu_adr[21:2]
cpu_acode[1:0]
cpu_cpr_sel
cpu_diu_sel
cpu_gpio_sel
cpu_icu_sel
cpu_lss_sel
cpu_pcu_sel
cpu_scb_sel
cpu_tim_sel
cpu_rom_sel
cpu_diu_sel
cpr_cpu_data[31:0]
diu_cpu_data[31:0]
gpio_cpu_data[31:0]
icu_cpu_data[31:0]
lss_cpu_data[31:0]
pcu_cpu_data[31:0]
scb_cpu_data[31:0]
tim_cpu_data[31:0]
rom_cpu_data[31:0]
pss_cpu_data[31:0]
pss_cpu_rdy
rom_cpu_rdy
tim_cpu_rdy
scb_cpu_rdy
pcu_cpu_rdy
lss_cpu_rdy
icu_cpu_rdy
gpio_cpu_rdy
diu_cpu_rdy
cpr_cpu_rdy
pss_cpu_berr
rom_cpu_berr
tim_cpu_berr
scb_cpu_berr
pcu_cpu_berr
lss_cpu_berr
icu_cpu_berr
gpio_cpu_berr
diu_cpu_berr
cpr_cpu_berr

FIG. 19


CPU Subsystem Bus Interface
RDU
MMU Control Block
Configuration Registers
LEON AHB Bridge
cpu_start_access
dram_access_en
cpu_rwn
cpu_mmu_adr[31:0]
cpu_dataout[31:0]
mmu_cpu_data[31:0]
mmu_cpu_rdy
cpu_mmu_acode[1:0]
mmu_cpu_berr
cpu_iack
cpu_adr[19:12]
peri_access_en
peri_mmu_data[31:0]
peri_mmu_rdy
peri_mmu_berr

FIG. 20


15
0
Write Mask
0
127
Write Data Buffer
21
4
Write Address Tag

FIG. 21


pclk
ahbsi.HADDR
A1
A2
A3
A4
ahbsi.CONTROL
LD
STD1
STD2
LD
ahbsi.HWDATA
BD1
BD2
ahbsi.HRDATA
RD1
ahbso.HREADY
cpu_diu_rreq
cpu_diu_rack
cpu_diu_rvalid
dram_cpu_data
LD1
cpu_diu_wadr
value determined by previous write
A2 value aligned on a 128-bit boundary
cpu_diu_wdata
value determined by previous writes
BD1
BD2 & BD1
cpu_diu_wmask
value determined by previous writes
000F
00FF
cpu_diu_wdatavalid
diu_cpu_write_rdy

FIG. 22


Proc
Cachemem
itag
idata
Cache_data_ram
dtag
ddata
Cache_data_ram
dram_cpu_data[255:0]
iline_rdy
icramo.icramout
icrami.icramin
dline_rdy
dcramo.dcramout
dcrami.dcramin
ahbsi
Cache
ICache
DCache
ACache
dcol
icol
mcdo
mcdi
ahbo
ahbi
mcio
mcii
ici
ico
dco
dci
oni
iuo
iui
Integer Unit
rfo
rfi
Register File

FIG. 23


dataout(31:0)
wordaddr(2:0)
RA032X32D2P2W1R1M3(7)
RA032X32D2P2W1R1M3(0)
rp_addr
wp_addr
dout(31:0)
din(31:0)
write
lineaddr(7:3)
addr(7:0)
lineaddr[7:3]
wordaddr[2:0]
line_refill
'1'
'0'
write
linedatain(255:224)
datain(31:0)
linedatain(31:0)

FIG. 24


cpr_cpu_debug_valid
diu_cpu_debug_valid
gpio_cpu_debug_valid
icu_cpu_debug_valid
lss_cpu_debug_valid
pcu_cpu_debug_valid
scb_cpu_debug_valid
tim_cpu_debug_valid
mmu_debug_valid
cpr_cpu_data[31:0]
diu_cpu_data[31:0]
gpio_cpu_data[31:0]
icu_cpu_data[31:0]
lss_cpu_data[31:0]
pcu_cpu_data[31:0]
scb_cpu_data[31:0]
tim_cpu_data[31:0]
mmu_debug_data[31:0]
DebugSrc Register
32
Debug Data0Src Register
Debug Data31Src Register
5
5
debug_data_valid
debug_data_out[0]
debug_data_out[31]
Debug PinSel Register
debug_cntrl[32:0]

FIG. 25


pclk
icu_cpu_ilevel[3:0]
0x0
0x5
0x0
cpu_icu_ilevel[3:0]
0x5
cpu_iack
icu_cpu_ilevel[3:0]
0x9
0x8
cpu_icu_ilevel[3:0]
0xA
0x9
cpu_iack

FIG. 26


replaceable ink cartridge
ink cartridge QA chip
ink
A3 Bi-lithic printhead
ink
A3 Bi-lithic printhead
ISI
Storage SoPEC Device #4
Printer QA chip
SoPEC Device #2
SoPEC Device #3
Printer QA chip
Printer QA chip
SoPEC Device #0
SoPEC Device #1
Printer QA chip
printhead assembly
USB Host
USB Device

FIG. 27


scb
scb_usbd
usb device core,
endpoint buffers
scb_usbh
usb host core,
read buffer,
write buffer
scb_isi
rx buffer, tx buffer,
serialiser,
de-serialiser
scb_ctrl
scb control logic,
scb map,
dma manager,
cpu tx buffer
usbd_ts
usbd_a
usbd_se0
usbd_zp
usbd_zm
usbd_z
usbh_cpr_reset_n
usbd_pull_up_en
usbd_vbus_sense
usbclk
usbh_ts
usbh_a
usbh_se0
usbh_zp
usbh_zm
usbh_z
usbh_over_current
usbh_power_en
isi_gpio_dout[3:0]
isi_gpio_e[3:0]
isi_cpr_reset_n
gpio_isi_din[3:0]
cpu_adr[n:2]
cpu_dataout[31:0]
scb_cpu_data[31:0]
cpu_scb_sel
cpu_rwn
cpu_acode[1:0]
scb_cpu_rdy
scb_cpu_berr
scb_cpu_debug_valid
dma_icu_irq
isi_icu_irq
usb_icu_irq[1:0]
scb_diu_wadr[21:5]
scb_diu_data[63:0]
scb_diu_wreq
diu_scb_wack
scb_diu_wvalid
scb_diu_wmask[7:0]
scb_diu_rreq
scb_diu_radr[21:5]
diu_scb_rack
diu_scb_rvalid
diu_data[63:0]
prst_n
pclk

FIG. 28


LEON CPU Bus
scb
scb_usbd
scb_ctrl
EP5 IN Buff
EP0 IN Buff
EP OUT
DMA Buffer
EP OUT
ISI Buffer
USB Device IP
PVCI Target
CPU
ISI Tx
Buffer
CPU i/f
SCB CSR
Control Core Logic
& SCB Map
DMA Manager
& DIU i/f
DIU Bus
USB
scb_usbh
scb_isi
USB Host IP
PVCI
Initiator
PVCI
Target
Read/Write Buffer
ISI Tx
Buffer
broadcast
ISI Rx
Buffer
Serialiser
Deserialiser
ISI i/f
ISI Core Logic
USB
ISI Bus
PC - DIU
PC - ISI
LEON - PC
ISI - DIU
LEON - ISI
Camera - DIU
DIU - Camera
LEON - Host IP
Host IP - LEON

FIG. 29


PCB#2
ISISlave SoPEC #1 (ISIId1)
D0
D1
ISISlave SoPEC #3 (ISIId3)
D0
D1
R
R
Flexy PCB
R
R
PCB#1
ISIMaster SoPEC (ISIId0)
D0
D1
ISISlave SoPEC #2 (ISIId2)
D0
D1

FIG. 30


ISISlave
D0Out
OutputEnable(=0)
D0In
D0Out
OutputEnable(=0)
D0In
b0
b2
b4
b6
b8
b10
b12
b14
b1
b3
b5
b7
b9
b11
b13
b15
ISIMaster Tx - ISISlave Rx
ISIMaster
D0Out
OutputEnable(=1)
D0In
D0Out
OutputEnable(=1)
D0In

FIG. 31



Transaction 1: Long packet to an addressed ISISlave



Transaction 2: Ping packet to an addressed ISISlave. ISISlave has nothing to send



Transaction 3: Ping packet to an addressed ISISlave. ISISlaveA responds with a long packet to ISISlaveB (or the ISIMaster) and ISISlaveB (or the ISIMaster) responds with an ACK or NAK.

FIG. 32


b0
b2
See PktDesc table
b0
4 bits
1 bit
b4
ISIId
ISISubId
b0
b288
Start
Pkt Desc
Address
Payload
CRC
Stop
8 bits
3 bits
5 bits
256 bits
16 bits
1 bit
Order of transmission

FIG. 33


b0
b2
See PktDesc table
b0
4 bits
1 bit
b4
ISIId
b1
b0
b32
Start
Pkt Desc
Address
CRC
Stop
8 bits
3 bits
5 bits
16 bits
1 bit
Order of transmission

FIG. 34


b0
b16
Start
Ack Symbol
Stop
8 bits
8 bits
1 bit
Order of transmission

FIG. 35


Transmitting ISI Device
Receiving ISI Device
0
seq = 0
0 -> 1
1
ACK
0 -> 1
1
seq = 1
1 -> 0
0
ACK
1 -> 0

FIG. 36


Transmitting
ISI Device
Receiving
ISI Device
0
seq = 0
0
0
seq = 0
0 -> 1
1
ACK
0 -> 1

FIG. 37


Transmitting
ISI Device
Receiving
ISI Device
0
seq = 0
0 -> 1
1
ACK
0
0
seq = 0
1
1
ACK
0 -> 1

FIG. 38


scb_isi
isi_ser_data_in[3]
isi_ser_data_out[3]
isi_ser_data_en[3]
isi_sie_3
isi_ser_data_in[2]
isi_ser_data_out[2]
isi_ser_data_en[2]
isi_sie_2
isi_ser_data_in[1]
isi_ser_data_out[1]
isi_ser_data_en[1]
isi_sie_1
isi_ser_data_in[0]
isi_ser_data_out[0]
isi_ser_data_en[0]
isi_sie_0
Framing
& CRC
ISI protocol
engine
ISI Tx FIFO
ISI Rx FIFO

FIG. 39


isi_sie
fifo_wr_tx
fifo_rd_rx
fifo_wr_data_tx
fifo_rd_data
fifo_count[2:0]
fifo_under_run
fifo_over_flow
Rx/Tx FIFO
7 x 1 bit
Rx/Tx statemachine
Bit stuffing
Edge detection
& data I/O
ser_data_en
rx_sample
tx_ready
tx_req
isi_bit_stuff_rate
ser_data_in
ser_data_out
isi_pclk
isi_reset_n

FIG. 40


ser_data_in_ff
ser_data_in
edge
PAD
stuff_0_en
fifo_rd_data
ser_data_out
1
0
stuff_1_en
ser_data_en
isi_sie

FIG. 41


sm_reset == 1
tx_ready = 0
ser_data_en = 0
rx_sample = 0
fifo_rd_tx = 0
fifo_reset = 0
rxtx_cycle = 0
strip_ack = 0
stuff_ack = 0
stuff_0_en = 0
stuff_1_en = 0
reset
sm_reset == 0
idle
tx_req == 1
fifo_reset = 1
clear
tx_ready = 1
wait
fifo_count != 0x0
tx_ready = 1
ser_data_en = 1
rxtx_cycle = 1
tx_req == 0
tx0
tx_req == 1
tx_ready = 1
ser_data_en = 1
rxtx_cycle = 1
tx4
tx_ready = 1
ser_data_en = 1
rxtx_cycle = 1
tx_req == 1
tx_ready = 1
ser_data_en = 1
fifo_rd_tx = 1
rxtx_cycle = 1
tx_req == 0
tx_ready = 1
ser_data_en = 1
fifo_rd_tx = 0
rxtx_cycle = 1
tx1
tx_ready = 1
ser_data_en = 1
rxtx_cycle = 1
tx2
tx_ready = 1
ser_data_en = 1
rxtx_cycle = 1
tx3

FIG. 42


stuff0_0
tx_req == 1
tx_ready = 1
ser_data_en = 1
rxtx_cycle = 1
stuff0_4
tx_ready = 1
ser_data_en = 1
rxtx_cycle = 1
stuff_0_en = 1
tx_ready = 1
ser_data_en = 1
rxtx_cycle = 1
stuff_0_en = 1
stuff_ack = 1
stuff0_1
tx_ready = 1
ser_data_en = 1
rxtx_cycle = 1
stuff_0_en = 1
stuff0_2
tx_ready = 1
ser_data_en = 1
rxtx_cycle = 1
stuff_0_en = 1
stuff0_3

FIG. 43


stuff1_0
tx_req == 1
tx_ready = 1
ser_data_en = 1
rxtx_cycle = 1
stuff1_4
tx_ready = 1
ser_data_en = 1
rxtx_cycle = 1
stuff_1_en = 1
tx_ready = 1
ser_data_en = 1
rxtx_cycle = 1
stuff_1_en = 1
stuff_ack = 1
stuff1_1
tx_ready = 1
ser_data_en = 1
rxtx_cycle = 1
stuff_1_en = 1
stuff1_2
tx_ready = 1
ser_data_en = 1
rxtx_cycle = 1
stuff_1_en = 1
stuff1_3

FIG. 44


idle
tx_req == 0 & edge == 1
rxtx_cycle = 1
rx0
edge == 0
rxtx_cycle = 1
tx_req == 0
rxtx_cycle = 1
tx_req == 1
rx1
edge == 1
rxtx_cycle = 1
rx4
edge == 0 &
strip == 1
strip_ack = 1
rxtx_cycle = 1
edge == 0 &
strip == 0
rx_sample = 1
rxtx_cycle = 1
edge == 0
rxtx_cycle = 1
rx2
edge == 0
rxtx_cycle = 1
rx3

FIG. 45


isi_pclk
tx_req
fifo_wr_tx
tx_ready
fifo_reset
fifo_count
0x0 0x1 0x2 0x3 0x4 0x5 0x6 0x7 0x6 0x7 0x6 0x7 0x6
rxtx_state
idle clear wait tx0 tx1 tx2 tx3 tx4 tx0 tx1 tx2 tx3 tx4 tx0 tx1 tx2 tx3 tx4 tx0 tx1 tx2 tx3 tx4 tx0
rx_tx_cycle
fifo_rd_tx
fifo_rd_data
bit0 bit1 bit2 bit3
ser_data_en
ser_data_out
bit0 bit1 bit2 bit3

FIG. 46


isi_pclk
ser_data_in_ff
tx_req
edge
rxtx_state
idle
rx0 rx1 rx2 rx3 rx4 rx0 rx1 rx2 rx3 rx4 rx0 rx1 rx2 rx3 rx4 rx0 rx1 rx2 rx3 rx0 rx1 rx2 rx3 rx4
rx_tx_cycle
rx_sample
fifo_count[2:0]
0x0
0x1
0x2
0x3
0x4
0x5

FIG. 47


fifo_wr_data
7 x 1 bit register
& decode
fifo_rd_data
fifo_wr_en
fifo_rd_en
rd/wr pointers,
& control logic
fifo_count[2:0]
fifo_reset

FIG. 48


rx_sample
fifo_wr_tx
a
b
z
fifo_wr_en
tx_ready
fifo_rd_rx
fifo_rd_tx
fifo_rd_en
ser_data_in_ff
fifo_wr_data_tx
fifo_wr_data

FIG. 49


sm_reset == 1
stuff_1 = 0
stuff_0 = 0
strip = 0
stuff_count_load = 0
reset
sm_reset == 0
idle
rx_tx_cycle == 1 &
tx_ready == 1 &
fifo_rd_data == 0
stuff_count_load = 1
rx_tx_cycle == 1 &
tx_ready == 1 &
fifo_rd_data == 1
stuff_count_load = 1
rx_tx_cycle == 0 ||
fifo_rd_data == 0
rx_tx_cycle == 0 ||
fifo_rd_data == 0
tx0
tx1
stuff_count == 0x1
stuff_1 = 1
stuff_count == 0x1
stuff_0 = 1
stuff_1 = 1
stuff1
stuff0
stuff_0 = 1
rx_tx_cycle == 0 ||
stuff_ack == 1
idle
rx_tx_cycle == 0 ||
stuff_ack == 1

FIG. 50


rx_tx_cycle == 1 &
tx_ready == 0 &
rx_sample == 1
ser_data_ff == 0 &
stuff_count_load = 1
idle
rx_tx_cycle == 1 &
tx_ready == 0 &
rx_sample == 1
ser_data_ff == 0 &
stuff_count_load = 1
rx_tx_cycle == 0 ||
tx_ready == 1 ||
rx_tx_cycle == 0 ||
tx_ready == 1 ||
rx0
ser_data_ff == 0
stuff_count_load = 1
rx1
ser_data_ff == 1
stuff_count_load = 1
strip = 1
stuff_count == 0x2
strip = 1
strip
stuff_count == 0x2
strip = 1
rx_tx_cycle == 0 ||
tx_ready == 1 ||
strip_ack == 1
idle

FIG. 51


15
12
11
5
4
0
Tx Data
Rx Data

FIG. 52


Master Clock
LEDDutySelect =0
LEDDutySelect =1
LEDDutySelect =2
LEDDutySelect =3
LEDDutySelect =4
LEDDutySelect =5
LEDDutySelect =6
LEDDutySelect =7

FIG. 54


DMAnTopAdr
DMAnIntAdr
DMAnCurrWPtr
DMAnMaxAdr
DMAnBottomAdr
(a)
DMAnTopAdr
DMAnMaxAdr
DMAnIntAdr
DMAnCurrWPtr
DMAnBottomAdr
(b)
Key:
Free buffer space
Filled buffer space (unprocessed data)
Buffer space filled since last write to the DMAnIntAdr/DMAnMaxAdr registers

FIG. 53


GPIO
interrupt_src_select
10x6
deglitch_out
24
mmi_ctrl_out
9
p_meas_int
2
Interrupt Select
10
gpio_icu_irq
24
wakeup_mask
1
wakeup_level
CPR Wakeup
gpio_cpr_wakeup
tim_pulse
x24
24
deglitch_out
24
deglitch_form_select
24x2
deglitch_select
2x8
deglitch_cnt
2x2
deglitch_clk_src
Input De-glitch
24
deglitch_input
Configuration registers
gpio_lss_din
2
lss_gpio_dout
2
lss_gpio_e
2
lss_gpio_clk
2
LSS
gpio_isi_din
4
isi_gpio_dout
4
isi_gpio_e
4
ISI
gpio_cpu_debug_valid
gpio_cpu_berr
2
cpu_acode
cpu_rwn
32
gpio_cpu_data
gpio_cpu_rdy
32
cpu_dataout
cpu_gpio_sel
9
cpu_adr
CPU
12
3
bldc_mode
3
bldc_direction
3
bldc_brake
BLDC Motor Control x3
3x6
bldc_ctrl
3
64
gpio_i
64
gpio_e
64
gpio_o
IO Control
3x16
motor_mas_count
3
motor_mas_clk_enable
6x2
motor_mas_clk_sel
6x32
motor_ctrl_config
3x16
motor_mas_clk_period
3x2
motor_mas_clk_src
3
motor_ctrl_cutout_en
Stepper Motor Control
6
motor_ctrl
usbh_gpio_power_en
gpio_usbh_over_current
USB host
3
tim_pulse
LED Pulse Gen
4x3
led_duty_sel
4
led_ctrl
64
io_pin_invert
64
cpu_io_dir
64
cpu_io_out
64
cpu_io_in
64x6
io_mode_select
24x6
input_pin_select
32
33
debug_data_out
debug_cntrl
debug_data_valid

FIG. 55


Configuration r gisters
Period Measure
x2
Multiple Media Interface (MMI)
IO Control
Frequency Modifier
To Interrupt Select
To Interrupt Select
gpio_phi_line_sync
deglitch_out[16,15]
p_meas_count
p_meas_last_period
wr_data
wr_count_en
wr_last_period_en
p_meas_int[0]
p_meas_last_period[0]
freq_mod_high
freq_mod_filt_coeff
freq_mod_bypass
freq_mod_filt_bypass
freq_mod_nco
freq_mod_out_div
freq_mod_k
freq_mod_k_div_out
freq_mod_mod_fest
freq_mod_nco_calc
mmi_rx_rd_data
mmi_rx_rd_en
mmi_wr_data
mmi_wr_add
mmi_tx_wr_en
mmi_mc_wr_en
mmi_tx_buf_mode
mmi_rx_buf_mode
mmi_tx_fill_level
mmi_rx_fill_level
mmi_ctrl_out
mmi_tx_data_o
mmi_data_en
gpio_i[63:0]
mmi_ser_dat_in
mmi_ctrl_in
degltich_out[3]
degltich_out[2:0],degltich_out[23:18]

FIG. 56


deglitch_out
deglitch_form_select
deglitch_input_ff
deglitch_input
tim_pulse[0]
tim_pulse[1]
tim_pulse[2]
1
cnt_en
Counter Logic
Compare
output_en
en
8
4x2
4x8
2
deglitch_clk_src[3:0]
deglitch_cnt[3:0]
deglitch_sel

FIG. 57


deglitch_out[13]
deglitch_out[14]
deglitch_out[15]
cut_out
motor_ctrl_cutout_en
motor_ctrl_config
motor_mas_clk_sel
x 3
x 6
motor_mas_clk_src
tim_pulse[0]
tim_pulse[1]
tim_pulse[2]
1
motor_mas_clk_period
motor_mas_clk_enable
cnt_en
Counter Logic
Phase Generator
mas_cnt
motor_ctrl
motor_mas_count
3x2
2
16
3x16
3
6
6x32
32
6x2

FIG. 58


Controller x 3
BLDC Controller Logic
ha
hb
hc
ext_direction
int_direction
pwm
mode
brake
q[5:0]
3x6
bldc_ctrl[2:0][5:0]
deglitch_out[8,4,0]
deglitch_out[9,5,1]
deglitch_out[10,6,2]
deglitch_out[11,7,3]
bldc_direction[2:0]
motor_ctrl[2:0]
bldc_mode[2:0]
bldc_brake[2:0]

FIG. 59


x 2
PeriodMeasure Logic
p_meas_pin
p_meas_pin_ff
1
24
24
24
24
2x24
2
2x24
p_meas_last_period
p_meas_int
p_meas_count
deglitch_out[17:16]
wr_data[31:0]
wr_last_period_en[1:0]
wr_count_en[1:0]
2
32
2
2
32

FIG. 60


gpio_phi_line_sync
1
div_ff
4
lsync_cnt_ff
8
Line Sync
Gen Logic
pin_in
pin_in_ff
1
4
freq_mod_out_div
8
freq_mod_high
deglitch_out[16]
nco_edge
freq_mod_bypass

FIG. 61


tim_icu_wd_irq
tim_icu_irq[2:0]
gpio_icu_irq[9:0]
usb_icu_irq[1:0]
isi_icu_irq
dma_icu_irq
lss_icu_irq[1:0]
cdu_finishedband
cdu_icu_jpegerror
lbd_finishedband
te_finishedband
pcu_finishedband
pcu_icu_address_invalid
phi_icu_page_finish
phi_icu_print_rdy
phi_icu_underrun
phi_icu_linesync_int
int_src
30
x30
Interrupt detect
int_active
30
int_pend
30
int_clear
30
int_config
30x7
cpu_int_clear
30
int_config[29:0][3:0]
Interrupt arbiter
4
icu_cpu_ilevel
30
Interrupt clear unit
4
cpu_icu_ilevel
cpu_iack
int_source
5
Configuration registers
2
cpu_acode
cpu_rwn
32
icu_cpu_data
icu_cpu_rdy
32
cpu_datаout
cpu_icu_sel
6
cpu_adr
icu_cpu_berr
icu_cpu_debug_valid
CPU

FIG. 62


reset==0
Idle
cpu_iack==1
cnt=NUM_INTS
curr_win=NoInterrupt
cnt !=0
cnt--
cnt == 0 AND curr_win==NoInterrupt
int_source=NoInterrupt
Compare
if (int_active[cnt] ==1) AND
(int_priority[cnt][3:0] ==cpu_icu_ilevel)
curr_win = cnt
cnt == 0 AND curr_win != NoInterrupt
int_source=curr_win
IntClear
cpu_int_clear[curr_win]=1
Machine remains in same state by default
All outputs are zero unless otherwise stated
State Description:
Idle : Normal Idle state
Compare: Compare interrupt level. Determines the interrupt source
IntClear: Interrupt clear, clear the pending bit for the current interrupt vector

FIG. 63


CPU
cpu_adr
cpu_tim_sel
cpu_dataout
tim_cpu_rdy
tim_cpu_data
cpu_rwn
cpu acode
tim_cpu_berr
tim_cpu_debug_valid
5
32
32
2
Configuration registers
pulse_timer_status
free_run_cnt
free_run_wen
timer_start_value
write_data
28
64
2
3x8
32
Timing pulse generator
tim_pulse[2:0]
Watchdog timer
wdog_tim_thres
wdog_unit_sel
wdog_wen
wdog_tim_cnt
32
3
32
32
tim_icu_wd_irq
tim_cpr_reset_n
Generic timers
gen_tim_en
gen_tim_auto
gen_unit_sel
gen_wen
gen_tim_cnt
gen_tim_cnt_st_value
32
3
3
3
3
3x32
3x32
tim_icu_irq[2:0]

FIG. 63A


wdog_unit_sel
2
tim_pulse[0]
tim_pulse[1]
tim_pulse[2]
1
cnt_en
wdog_wen
write_data
32
Counter Logic
wdog_tim_thres
32
Timer Decode
32
tim_icu_wd_irq
tim_cpr_reset_n
wdog_tim_cnt

FIG. 64


gen_unit_sel
2
tim_pulse[0]
tim_pulse[1]
tim_pulse[2]
1
cnt_en
gen_tim_en
gen_tim_cnt_st_value
32
gen_wen
write_data
gen_tim_en
gen_tim_auto
Counter Logic
Timer Decode
tim_icu_irq
gen_tim_cnt

FIG. 65


Free Run Timer
free_run_wen
2
free_run_data
32
Increment Logic
64
64
free_run_cnt
Timer 0
timer_start_value[0]
8
Decrement Logic
8
Compare
tim_pulse[0]
tim_pulse[0]
Timer 1
tim_pulse[0]
timer_start_value[1]
8
Decrement Logic
8
Compare
tim_pulse[1]
tim_pulse[1]
Timer 2
tim_pulse[1]
timer_start_value[2]
8
Decrement Logic
8
Compare
pulse_
tim_pulse[2]
27
pulse_timer_status
tim_pulse[2:0]

FIG. 66


1.04ns
PLL Master Clock
clk320
clk320 PLL phase shift
doclk
doclk insertion delay
clk160
clk160 PLL phase shift
pclk
jclk
pclk/jclk insertion delay

FIG. 67


bufrefclk domain clock generator
Clock driver
xtalin
xtalout
Crystal Oscillator
PLL
pll_outa
pll_outb
sync
Clock Gate
clk96
/2
clk48
clk320
clk160
usbclk
master_pclk
bufrefclk
pll_reset
clk_gate
reset_n
deglitch
reset_n_deglitch
PLL control state machine
reset_dg_n
gate_dom[3]
gate_dom[4]
gate_dom[0]
gate_dom[1]
gate_dom[2]
gate_dom[5]
doclk
pclk_section[0]
pclk_section[1]
pclk_section[2]
pclk_section[3]
jclk
usb_cpr_reset_n
isi_cpr_reset_n
tim_cpr_reset_n
jclk_enable
gpio_cpr_wakeup
Reset + Sleep Logic
sleep_mode_en
reset_section_stat
reset_section_n
cfg_reset_n
pll_control
pll_update
pll_update_com
Configuration registers
cpu_adr
cpu_cpr_sel
cpu_dataout
cpr_cpu_rdy
cpr_cpu_data
cpu_rwn
cpu_acode
cpr_cpu_berr
cpr_cpu_debug_valid
CPU
Sync
reset_dom[3]
reset_dom[0]
reset_dom[1]
reset_dom[2]
reset_dom[4]
reset_dom[5]
usbrst_n
prst_n_section[0]
prst_n_section[1]
prst_n_section[2]
prst_n_section[3]
dorst_n
jrst_n

FIG. 68


bufrefclk
reset_n
reset_n_int
cnt
reset_dg_n
reset_n
synchronizer
reset_n_int
Counter Logic
ctr
Compare = 31
reset_n_deglitch
Note: All FF's are clocked on bufrefclk

FIG. 69


usbclk
reset_dom
usbrst_n
synchronizer
1
1
usbrst_n
reset_dom
usbclk

FIG. 70


src_clk
gate_dom
gate_dom_retimed
gate_clock
gate_dom_retimed
gate_clock
1
gate_dom
src_clk

FIG. 71


clk48
clk320
clk160
Clock Divider A
Clock Divider B
pllouta & plloutb are gated when the PLL is out of lock
clock gating
clock gating
sync
sync
pll_outa
pll_outb
bufrefclk
clk_gate
pll_update_com
reset_dg_n
fbkclk
PLL
pll_reset
PLL control state machine
refclk
21
rst
pll_cfg_reset_n
sync
Crystal Oscillator
xtalin
xtalout
pclk domain
pll_rangea
pll_rangeb
pll_multiplier
pll_tune
pll_update
reset_n_deglitch
deglitch
reset_n
Note: All logic clocked on bufrefclk unless otherwise indicated

FIG. 72


reset_n_deglitch==0
RstStart
pll_reset=1
clk_gate =1
pll_cfg_reset_n =0
RstLockCtr
clk_gate =1
pll_lockctr ++
pll_lockctr ==0xC80
pll_lock_ctr=0
RstClksOn
reset_dg_n = 0
pll_lockctr ++
pll_lockctr ==0x5
pll_lock_ctr=0
Normal
pll_update == 1
CfgClksOff
clk_gate =1
pll_lockctr ++
pll_lockctr ==0x5
pll_lock_ctr=0
CfgPllUpdate
pll_reset=1
pll_cfg_update = 1
clk_gate =1
pll_lockctr ++
pll_lockctr ==0x5
pll_lock_ctr=0
CfgLockCtr
clk_gate =1
pll_lockctr ++
pll_lockctr ==0xC80
pll_lock_ctr=0
CfgUpdateClr
pll_update_com=1
pll_lockctr ++
pll_lockctr ==0x5
pll_lock_ctr=0
Default Outputs
pll_reset =0
clk_gate = 0
pll_cfg_reset_n = 1
reset_dg_n = 1
pll_update_com=0
pll_cfg_update = 0

FIG. 73


CPU Bus Interface
cpu_adr
rom_cpu_data
cpu_rom_sel
cpu_rwn
rom_cpu_rdy
cpu_acode
rom_cpu_berr
14
32
2
rom_adr
12
rom_data
32
fuse_data
32
fuse_reg_adr
3
ROM Macro
4096 x 32
IBM 112bit ECID macro
FUSE000
FUSE001
FUSE111
Custom 112bit ECID macro
FUSE00
FUSE01
FUSE111

FIG. 74


CPU sub-system bus
CPU
LSS Master
GPIO
SoPEC
LSS bus 0
LSS bus 1
QA Chip 0
QA Chip 1
QA Chip 2
QA Chip 3

FIG. 75


lss_data
lss_clk
S
START
CONDITION
P
STOP
CONDITION

FIG. 76


lss_data
lss_clk
S
START
condition
1 - 7
ID byte[7:1]
8
R/W
9
ACK
bits 7 - 1
bit 0
Ack
DATA
Nack
P
STOP
condition

FIG. 77


Byte 0
Byte M-1
Byte M
S
ID byte[7:1]
0
A
Data(8)
A
Data(8)
A
Data(8)
A
P
S = Start condition
A = Ack
N = Nack
P = Stop condition
Shaded bits driven by slave

FIG. 78


Byte 0
Byte 1
Byte M
S
ID byte[7:1]
1
A
Data(8)
A
Data(8)
A
Data(8)
N
P
S = Start condition
A = Ack
N = Nack
P = Stop condition
Shaded bits driven by slave

FIG. 79


CPU
cpu_rwn
cpu_adr[6:2]
cpu_lss_sel
cpu_acode
cpu_dataout
lss_cpu_rdy
lss_cpu_data
lss_cpu_berr
lss_cpu_debug_valid
Low Speed Serial Interface
5
2
32
32
configuration registers
lss0_cmd
lss0_new_cmd
lss0_status
lss0_current_state
lss0_buffer_rdata
lss0_buffer_wen
lss0_buffer_wrdata
lss_clk_to_data_hold
lss_clk_highlow_duration
6
16
lss1_cmd
lss1_new_cmd
lss1_status
lss1_current_state
lss1_buffer_rdata
lss1_buffer_wen
lss1_buffer_wrdata
22
3
4
5x32
5
32
Clock Gen
lss_clk
lss_input_strobe
lss_output_release
LSS bus 0 master unit
LSS bus 1 master unit
1
1
2
lss_gpio_clk[0]
lss_gpio_e[0]
lss_gpio_dout[0]
gpio_lss_din[0]
lss_gpio_clk[1]
lss_gpio_e[1]
lss_gpio_dout[1]
gpio_lss_din[1]
lss_icu_irq
GPIO
ICU

FIG. 80


Tp
lss_clk_int
lss_clk
lss_data
lss_cmd
7.... 0
7.... 0
Start
Idle
Send Byte and (n)ack
Idle
Send Byte and (n)ack
Idle
Stop

FIG. 81


Start Condition
Stop Condition
Bus state case 1
(lss_clk=1,lss_data=1)
Bus state case 2
(lss_clk=1,lss_data=0)
Bus state case 3
(lss_clk=0,lss_data=1)
Bus state case 4
(lss_clk=0,lss_data=0)
lss_clk_int
lss_data
lss_clk

FIG. 82


Reset OR prst_n == 0
State machine outputs, lss_icu_irq and LssStatusSet are zero unless otherwise indicated.
Reset
Wait
lss_new_cmd == 1 AND Start == 0 AND IdByteEnable == 0 AND RdWrEnable == 0 AND Stop == 0
lss_new_cmd == 1 AND Start == 1
lss_new_cmd == 1 AND Stop == 1 AND RdWrEnable == 1 AND IdByteEnable ==0
GenerateStart
lss_new_cmd == 1 AND Start == 0 AND
Check IdByteEnable
IdByteEnable == 1
SendIdByte
IdByteEnable == 0
nack_detect == 1 lss_status_set[1] = 1 lss_icu_irq = 1
WaitForIdAck
AckDetect == 1
RdWrEnable == 1 AND RdWrSense == 0 count =TxRxByteCount
RdWrEnable == 1 AND RdWrSense == 1 count =TxRxByteCount
TransmitByte
Check RdWrEnable
ReceiveByte
count == 1 AND ReadNack == 1
count > 1 OR ReadNack == 0
count > 1 count –
ack_detect == 1 AND count > 1 count –
RdWrEnable == 0 OR TxRxByteCount=0
SendNack
SendAck
ack_detect == 1 AND count == 1
WaitForAck
CheckStop
count == 1
Stop == 1
nack_detect == 1 lss_status_set[2] = 1 lss_icu_irq = 1
Stop == 0 lss_status_set[0] = 1 lss_icu_irq = 1
GenerateStop
lss_status_set[0] = 1 lss_icu_irq = 1
Generate Interrupt

FIG. 83


free running
400Khz clock
Tp
Tp
Iss_clk
Iss_data
Start Condition
Tstart_delay
Tdata_setup
D1
Tdata_hold
D2
Tack_setup
Ack/Nack
Tstrobe
Tack_hold
Stop Condition
Tstop_delay

FIG. 84


CPU sub-system
DRAM sub-system
eDRAM
DIU
DRAM bus
Print Engine Pipeline sub-system
CPU
RDU
MMU
Master
Slave
TIM
Boot ROM
ICU
PSS
Slave
SCB
USB Host
USB PHY
USB Device
DMA Crtl
ISI
Bus
CPU Subsystem
CPR
GPIO
Motor Control, LSS, ISI, LED, etc.
LSS Master
PCU
Master
PEP Configuration Bus
CDU
CFU
LBD
SFU
TE
TFU
HCU
DNC
DWU
LLU
PHI
Bi-lithic Printhead

FIG. 85


pclk
diu_data[63:0]
access n
access n+1
access n+2
unused cycle
access
unused cycle
access
unused cycle
access
rreq(n+1)
rreq(n+2)
rreq(n+3)
rack(n+1)
rack(n+2)
rack(n+3)

FIG. 86


pclk
non-CPU read access
CPU read access
non-CPU read access
CPU read access
diu_data[63:0]
dram_cpu_data[255:0]

FIG. 87


pclk
Read access
Write access
Read access
Write access
256-bit buffered write data for SoPEC Unit n
diu_data[63:0]
256-bit buffered write data for SoPEC Unit m

FIG. 88


pclk
Write access
Write access
Write access
256-bit buffered write data for SoPEC Unit n
256-bit buffered write data for SoPEC Unit m
256-bit buffered write data for SoPEC Unit p

FIG. 89


pclk
<unit>_diu_rreq
diu_<unit>_rack
<unit>_diu_radr[21:5]
diu_<unit>_rvalid
diu_data[63:0]
1
2
3
4

FIG. 90


pclk
cpu_diu_rreq
diu_cpu_rack
cpu_adr[21:5]
diu_cpu_rvalid
dram_cpu_data[255:0]

FIG. 91


pclk
<unit>_diu_wreq
<unit>_diu_wadr[21:5]
diu_<unit>_wack
<unit>_diu_data[63:0]
1
2
3
4
scb_diu_wmask[7:0]
(SCB writes only)
1
2
3
4
<unit>_diu_wvalid

FIG. 92


pclk
diu_cpu_write_rdy
cpu_diu_wdatavalid
cpu_diu_wadr[21:4]
cpu_diu_wdata[127:0]
cpu_diu_wmask[15:0]
posted write buffer full
full
posted write occurs later
3-cycle write to DRAM

FIG. 93


pclk
cdu_diu_wreq
cdu_diu_wadr[21:3]
diu_cdu_wack
cdu_diu_data[63:0]
1
2
3
4
cdu_diu_wvalid

FIG. 94



FIG. 95



FIG. 100


current timeslot pointer
write timeslot lookahead pointer
n
n+1
n+2

FIG. 96


W R W R W
Programmed timeslot order
W W R W R
Timeslot arbitration order
W R W R W
Actual timeslot order
write latency

FIG. 97


R W R R W
Programmed timeslot order
RW R W R
Timeslot arbitration order
R W R R W
Actual timeslot order
write latency

FIG. 98


R R W R W
Programmed timeslot order
R W R W R
Timeslot arbitration order
R R W R W
Actual timeslot order
initial write latency

FIG. 99


DRAM Arbitration Unit (DAU)
CPU Configuration and Arbitration Logic
Command Multiplexor
Read and Write Data Multiplexor
DRAM Controller Unit (DCU)
cpu_rwn
cpu_diu_sel
cpu_adr[10:2]
cpu_dataout[31:0]
cpu_rwn
cpu_acode[1:0]
diu_cpu_data[31:0]
diu_cpu_rdy
diu_cpu_berr
diu_cpu_debug_valid
<unit>_diu_rreq
<unit>_diu_wreq
2 write_cmd_rdy
2 read_cmd_rdy
n other DAU IO for debug
5 read_sel
read_complete
5 write_sel
write_complete
dau_dcu_reset_n
dau_dcu_msn2stall
dcu_dau_refreshcomplete
re_arbitrate
re_arbitrate_wadv
arb_gnt 2
5 arb_sel
dir_sel
diu_<unit>_rack
<unit>_diu_radr[21:5]
diu_<unit>_wack
<unit>_diu_wadr[21:5]
scb_diu_wmask[7:0]
cdu_diu_wadr[21:3]
cpu_adr[21:0]
cpu_diu_wmask[1:0]
dcu_dau_adv
dcu_dau_wadv
dau_dcu_refresh
dau_dcu_adr 17
dau_dcu_rwn
dau_dcu_cduwpage
dau_dcu_wmask 32
dau_dcu_wdata 256
256 wdata
32 cpu_wdata
5 write_sel
write_complete
write_data_valid 2
write_data_accept 2
dram_cpu_data[255:0]
diu_data[63:0]
diu_<unit>_rvalid
cpu_dataout[31:0]
<unit>_diu_data[63:0]
<unit>_diu_wvalid
dcu_dau_rvalid
dcu_dau_rdata256
256 wdata
32 cpu_wdata
2 write_cmd_rdy
2 read_cmd_rdy
5 read_sel
read_complete

FIG. 101


dcu_dau_rdata
256
0
1
inst0_DO
inst1_DO
256
256
10 Mbit DRAM Instance0
10 Mbit DRAM Instance1
MSN
A
A
MSN
inst0_MSN
inst1_MSN
SEL 0
SEL 1
dau_dcu_refresh
MSN
16
16
16
A[15:0]
MSN
dau_dcu_refresh
instance_sel
next_cmdadr[21:5]
Address Translation & Instance Decode
17
cmdadr[21:5]
dau_dcu_adr[21:5]
dau_dcu_valid
pagemode_adr_inc

FIG. 102


pclk
dcu_dau_adv
DRAM address
adr1
adr2
adr3
adr4
dcu_statemachine
rst
msn1
msn2
rst
msn1
msn2
rst
msn1
msn2
rst
msn1
msn2
dcu_dau_wadv

FIG. 103


reset=0
RST
MSN = 1, PGN = 1
WEN = dau_dcu_rwn OR NOT dau_dcu_refresh
REFN = NOT dau_dcu_refresh
DI = dau_dcu_wdata
BW = bitwritemask
dcu_dau_wadv = NOT dau_dcu_cduwpage
dcu_dau_rvalid = 0
pagemode_adr_inc = 0
pagewritecount = 0
dcu_dau_refreshcomplete = 0
dau_dcu_valid==1
MSN1
MSN = 0, PGN = 0
dcu_dau_adv = 0
dau_dcu_cduwpage == 1
AND dau_dcu_msn2stall == 0
MSN2
MSN = 0, PGN = 0
dcu_dau_adv = NOT dau_dcu_cduwpage
dcu_dau_rvalid = dau_dcu_rwn AND
NOT dau_dcu_refresh
pagemode_adr_inc = dau_dcu_cduwpage
dcu_dau_refreshcomplete = dau_dcu_refresh
dau_dcu_cduwpage == 0
AND dau_dcu_msn2stall == 0
PAGE RESTORE
MSN = 0, PGN = 1
dcu_dau_rvalid = 0
pagemode_adr_inc = 0
pagewritecount ++
pagewritecount!=3
PAGE ACTIVE
MSN = 0, PGN = 0
dcu_dau_wadv = (pagewritecount==2)
dcu_dau_adv = (pagewritecount==3)
pagemode_adr_inc = 1
pagewritecount==3

FIG. 104


0ns
10ns
20ns
30ns
PCLK
MSN
A15.A03
A02.A00
PGN
WEN
DO
state
dcu_dau_adv
Tcyc
Tres
Tact
RA0
CA0
Tmprd
Tacc
D0
RST
RST
MSN1
MSN2
RST

FIG. 105


0ns
10ns
20ns
30ns
PCLK
MSN
A15.A03
A02.A00
PGN
WEN
DI
BW
state
dcu_dau_adv
Tcyc
Tact
Tres
Tmprd
RA0
CA0
D0
BW
RST
RST
MSN1
MSN2
RST

FIG. 106


0ns
10ns
20ns
30ns
PCLK
MSN
WEN
REFN
state
dcu_dau_adv
Trfc
Tact
Tres
RST
RST
MSN1
MSN2
RST

FIG. 107


0ns
25ns
50ns
PCLK
MSN
PGN
WEN
A15.A03
A02.A00
DI
BW
state
dcu_dau_adv
Tactp
Tpamr
Tres
Tmprd
Tpr
Tpa
Tpcyc
RA0
CA0
CA1
CA2
CA3
D0
D1
D2
D3
BW0
BW1
BW2
BW3
RST
MSN1
MSN2
PR
PA

FIG. 108


pclk
<unit>_diu_rreq
<unit>_diu_radr[21:5]
registered request in DAU Arbitration Logic
dcu_dau_adv / re_arbitrate
DRAM address
adr1
Stand-alone Read...
DRAM read
dcu_statemachine
rst
msn1
msn2
rst
msn1
msn2
rst
msn1
msn2
rst
diu_<unit>_rack
diu_data[63:0]
data1
data2
data3
data4
diu_<unit>_rvalid
Back-to-Back Reads...
<access other than>
< a non-CPU read >
< DRAM read 1 > < DRAM read 2 >
dcu_statemachine
rst
msn1
msn2
rst
msn1
msn2
rst
msn1
msn2
msn2
rst
msn1
diu_<unit 1>_rack
diu_<unit 2>_rack
diu_data[63:0]
data1
data2
data3
data4
data1
data2
diu_<unit 1>_rvalid
diu_<uni t 2>_rvalid

FIG. 109


pclk
cpu_diu_rreq
diu_cpu_rack
cpu_adr[21:5]
un-registered request in DAU Arbitration Logic
dcu_dau_adv / re-arbitrate
DRAM address
adr1
DRAM read
dcu_statemachine
rst
msn1
msn2
rst
msn1
msn2
rst
dram_diu_data[255:0]
data1
diu_cpu_rvalid

FIG. 110


CPU MMU logic delay
CPU generates request
Arbitration occurs
cycle 1
DCU Address setup cycle (RST)
cycle 2
DRAM access (MSN1)
Tacc = 8 ns
cycle 3
DRAM access (MSN2)
cycle 4
CPU captures read data in AHB bridge
cycle 5
CPU MMU logic delay
CPU generates request
Arbitration occurs
cycle 6

FIG. 111


pclk
diu_cpu_write_rdy
cpu_diu_wdatavalid
cpu_diu_wadr[21:5]
cpu_wmask[1:0]
cpu_diu_wdata[127:0]
posted write buffer
posted write request in DAU
dcu_dau_adv
DRAM address
DRAM data
DCU state machine
1
2
3
4
5
6
adr
DRAM write
msn2
rst
msn1
msn2
rst
msn1
msn2
rst
msn1
msn2
rst

FIG. 112


pclk
sfu_diu_wreq
diu_sfu_wack
sfu_diu_wadr[21:3]
sfu_diu_data[63:0]
sfu_diu_wvalid
registered request in DAU Arbitration Logic
dcu_dau_wadv
dcu_dau_adv
DRAM address
DCU state machine
DRAM data
1
2
3
4
5
6
7
8
9
1
2
3
4
adr1
msn1
msn2
rst
msn1
msn2
rst
msn1
msn2
rst
msn1
msn2
rst
DRAM write
data

FIG. 113


pclk
cdu_diu_wreq
diu_cdu_wack
cdu_diu_wadr[21:3]
cdu_diu_data[63:0]
cdu_diu_wvalid
registered request in DAU Arbitration Logic
dcu_dau_wadv
dcu_dau_adv
DRAM address
DCU state machine
DRAM data
rst
6-cycle push-out
6-cycle push-out
DRAM write
1
2
3
4
msn1 msn2 rst msn1 msn2 rst msn1 msn2 rst msn1 msn2 pr pa pr pa pr pa pr rst
adr 1 adr 2 adr 3 adr 4
data 1 data 2 data 3 data 4

FIG. 114


to CPU Interface sub-block
DRAM Controller Unit
write_sel[4:0]
dau_dcu_adr[21:5]
dau_dcu_rwn
dau_dcu_cduwpage
dau_dcu_refresh
dcu_dau_adv
dau_dcu_wdata[255:0]
dau_dcu_wmask[31:0]
re_arbitrate
re_arbitrate_wadv
write_cmd_rdy[1:0]
read_cmd_rdy[1:0]
write_data_valid[1:0]
write_data_accept[1:0]
write_complete
cmd issuing logic
re-arbitration logic
29
0
1
adr
arb_sel
dir_sel
advance command register
adr[21:0]
arb_sel[4:0]
dir_sel[1:0] = 00
ack
Command Multiplexor Control Logic
steering multiplexor
<unit>_diu_*adr
diu_<unit>_*ack
dir_sel[1:0]
SoPEC Unit 1
SoPEC Unit 2
SoPEC Unit n
arb_gnt
arb_sel[4:0]
dir_sel[1:0]
cpu_wmask
16
wdata
256
cpu_wdata
128

FIG. 115


pclk
re_arbitrate
arb_gnt /
diu_<unit>_*ack
arb_sel[3:0]
adr[21:0]
dau_dcu_adr
dau_dcu_valid
arb_sel1
arb_sel3
adr1
adr3
adr1
adr3

FIG. 116


pclk
DCU state machine
re_arbitrate
re_arbitrate_wadv
msn2
rst
msn1
msn2
rst
msn1
msn2
rst
msn1
msn2
rst
msn1

FIG. 117


cpu_access
<unit>_diu_rreq
10
<unit>_diu_wreq
4
Arbitration Logic
arb_gnt
cpu_diu_rreq
diu_cpu_write_rdy
dau_dcu_msn2stall
re_arbitrate
re_arbitrate_wadv
read_cmd_rdy[1:0]
write_cmd_rdy[1:0]
arb_sel
dir_sel
configuration
n
cpu_rwn
cpu_diu_sel
cpu_adr[10:2]
cpu_dataout[31:0]
cpu_acode[1:0]
diu_cpu_data[31:0]
diu_cpu_rdy
diu_cpu_berr
diu_cpu_debug_valid
CPU Interface and Configuration Registers
refresh_ack
refresh_req
cpu_sel
Refresh Controller
refresh_period
CPUPreAccessTimeslots
CPUTotalTimeslots
RotationSync
CPU Timeslots Controller
debug signals n

FIG. 118


pclk
re_arbitrate
arb_gnt
arb_sel[3:0]
0000
1000
00001
dir_sel[1:0]
10
01
10

FIG. 119


pclk
cpu_diu_sel
1- to 3-cycle delay to
align rdy to new rotation
diu_cpu_rdy
cpu_dataout[31:0]
DIU config data
RotationSync
arbitrate
arbitrate
arbitrate
arbitrate
DCU
state machine
rst
msn1
msn2
rst
msn1
msn2
rst
msn1
msn2
rst
msn1
msn2
rst
msn1
CPU accesses & refreshes only
refresh
CPU pre-access
or refresh
1st non-CPU
access of
new rotation
preamble

FIG. 120



FIG. 121



FIG. 122



FIG. 123



FIG. 124



FIG. 125


CPU
SoPEC Unit 1
SoPEC Unit 2
SoPEC Unit n
dram_cpu_data
256
diu_cpu_rvalid
64
diu_data
diu_<unit1>_rvalid
diu_<unit2>_rvalid
diu_<unitn>_rvalid
read_sel
5
read_complete
read_cmd_rdy
2
read_type
shared read data buffer
select shared_rvalid
noncpu_rvalid
Read Multiplexor control logic
address_match
dcu_dau_rvalid
dcu_dau_rdata
non-CPU write
data buffer
arb_gnt
arb_sel
4
dir_sel

FIG. 126


pclk
dcu_dau_rvalid
dcu_dau_rdata[255:0]
cpu
cdu
cpu
diu_cpu_rvalid
dram_cpu_data[255:0]
cpu
cpu
diu_cdu_rvalid
diu_data[63:0]
cdu1
cdu2
cdu3
cdu4

FIG. 127



FIG. 128



FIG. 129


pclk
dcu_dau_rvalid
dcu_dau_rdata[255:0]
cdu
cdu
cdu
diu_cpu_rvalid
256 bits written to shared read data buffer
256 bits written to shared read data buffer
256 bits written to shared read data buffer
dram_cpu_data[255:0]
diu_cdu_rvalid
diu_data[63:0]
cdu1 cdu2 cdu3 cdu4 cdu1 cdu2 cdu3 cdu4 cdu1 cdu2 cdu3 cdu4
no. 64-bit words in shared read data buffer
0 4 3 2 1 4 3 2 1 4 3 2 1
read_cmd_rdy[1]
dcu_statemachine
msn1 msn2 rst msn1 msn2 msn2 rst msn1 msn2 msn2 rst msn1 msn2 msn2
dau_dcu_msn2stall

FIG. 130


CPU
SoPEC Unit
SoPEC Unit
cpu_diu_wdata
128
diu_cpu_write_rdy
cpu_diu_wdatavalid
control logic
Posted CPU
write data buffer
128
Non-CPU
write data buffer
128
cpu_wdata
non_cpu_wdata
256
64
64
64
64
64
64
64
64
64
64
<unit2>_diu_data
<unit2>_diu_wvalid
<unitn>_diu_data
<unitn>_diu_wvalid
2
5
write_sel
wvalid
word_sel
Write Multiplexor Control Logic
write_data_valid
2
write_cmd_rdy
2
arb_gnt
arb_sel
5
dir_sel
2
write_data_accept
2

FIG. 131


TE
LBD
CDU
te_finishedband
lbd_finishedband
cdu_finishedband
end of band unit
PEP controller unit
Interrupt Controller Unit (ICU)
pcu_finishedband
pcc_icu_addressInvalid
state machine
control
address
data
17
64
DRAM interface
XXX_pcu_rdy
XXX_pcu_data
pcu_XXX_sel
pcu_dataout
pcu_adr
pcu_rwn
32
32
10
cpu_adr
cpu_dataout
pcu_cpu_data
cpu_rwn
cpu_pcu_sel
pcu_cpu_rdy
cpu_acode
pcu_cpu_berr
pcu_cpu_debug_valid
14
32
32
2
CPU

FIG. 132


Write
Read
pclk
pcu_adr[13:2]
PEP address
PEP address
pcu_rwn
pcu_<block0>_sel
<block0>_pcu_rdy
pcu_dataout[31:0]
PEP data
pcu_<block1>_sel
<block1>_pcu_rdy
<block1>_pcu_data[31:0]
PEP data

FIG. 133


State Machine A
pcu_softreset_n == 0 OR prst_n == 0
Reset
pcu_softreset_n == 1
AND prst_n == 1
<unit>_pcu_rdy == 1
AND cmd_fifo_full !=0
cmd_count –
Arbitrate
cpu_pcu_sel==1 AND
cpu_acode != 11
pcu_cpu_berr=1
<unit>_pcu_rdy == 1
pcu_cpu_rdy = 1
pcu_cpu_data = <unit>_pcu_data
cmd_source==1 AND
cmd_fifo_full==1
cpu_pcu_sel == 1
AND cpu_acode == 11
DRAMAccess
CpuAccess
cmd_source==1 AND
cmd_fifo[cmd_count]==RESERVED
cmd_fifo_full=0
cmd_fifo=0
cmd_source=0
AdrError
pcu_icu_address_invalid=1

FIG. 134


State Machine B
pcu_softreset_n == 0 OR prst_n == 0
Reset
pcu_softreset_n == 1
AND prst_n == 1
Wait
cmd_source==0 AND cmd_fifo_full==0
AND cmd_pending !=0
cmd_source = 1
pcu_diu_rreq=1
cmd_adr = NextBandCmdAdr[pending]
pcu_diu_radr=cmd_adr
cmd_source==1 AND cmd_fifo_full==0
pcu_diu_rreq=1
pcu_diu_radr=cmd_adr
Ack
diu_pcu_rack==1
pcu_diu_rreq=0
FillFifo
diu_pcu_rvalid==1
cmd_fifo[3]=diu_data
Data1
diu_pcu_rvalid==1
cmd_fifo[2]=diu_data
Data2
diu_pcu_rvalid==1
cmd_fifo[1]=diu_data
Data3
diu_pcu_rvalid==1
cmd_fifo[0]=diu_data
cmd_fifo_full=1
cmd_count = 3
invalid_address[21:5]=cmd_adr
cmd_adr++
Default (from all states except WAIT and RESET)
cmd_source==0
STATE = WAIT

FIG. 135


eDRAM
compressed contone planes
bytestream
Contone Decoder Unit (writes blocks)
blocks
decompressed contone line store buffer (minimum 12 lines)
lines
Contone Fifo Unit (reads lines)

FIG. 136


DRAM Interface Unit
diu_data
cdu_diu_rreq
cdu_dwu_radr
diu_cdu_rack
diu_cdu_rvalid
cdu_diu_data
cdu_diu_wreq
diu_cdu_wack
cdu_dwu_wadr
cdu_diu_wvalid
64
end_of_band
17
64
17
compressed contone FIFO
2
rd_en, wr_en
3
fifo_wr_adr
6
fifo_rd_adr
read control unit
write control unit
jpg_in_strb
jpg_in_rdy
jpg_in
8
17
19
3
17
17
2
13
30
curr_source_adr
end_source_adr
valid_bytes_last_fetch
start_of_bandstore
end_of_bandstore
max_plane
max_block
buff_start_adr, buff_end_adr
half_block_ok_to_read
rd_adv
rd_adv_half_block
line_store_ok_to_write
wradv8line
JPEG decoder
jpg_dec_status
configuration registers
contone line store interface
num_buff_lines
7
bypass_jpg
pixel_out_valid
half-block buffer interface
pixel_out
8
8
0
1
8
jclk
Contone Decoder Unit
6
32
32
pcu_cdu_sel
pcu_rwn
pcu_adr
pcu_dataout
cdu_pcu_rdy
cdu_pcu_datain
jclk
jclk_enable
cfu_cdu_rdadvline
cdu_cfu_linestore_rdy
PEP Controller Unit
Clock, Power Reset
Contone Fifo Unit

FIG. 137


Reset OR prst_n == 0
cdu_diu_rreq = 0
ignore_data = 0
reset
Go == 0
cdu_diu_rreq = 0
ignore_data = 0
idle
Go == 1 AND
DoneBand == 0
cdu_diu_rreq = 0
ignore_data = 0
req
fifo_contents <= (fifo_size - 4)
cdu_diu_rreq = 1
ignore_data = 0
{curr_source_adr.rd_count} ==
end_source_adr
cdu_diu_rreq = 0
ignore_data = 1
curr_source_adr != end_source_adr[18:2]
AND rd_count == 3
cdu_diu_rreq = 0
ignore_data = 0
ack
diu_cdu_rack == 1
cdu_diu_rreq = 0
ignore_data = 0
read

FIG. 138


DRAM
DRAM word p
DRAM word p+4
DRAM word p+4n
4 line store
JPEG block 0 lines 0 to 3
JPEG block 1 lines 0 to 3
JPEG block n lines 0 to 3
255 191 127 63 0
C3L0 C2L0 C1L0 C0L0 word p
C3L1 C2L1 C1L1 C0L1 word p+1
C3L2 C2L2 C1L2 C0L2 word p+2
C3L3 C2L3 C1L3 C0L3 word p+3
DRAM word q
DRAM word q+4
DRAM word q+4n
4 line store
JPEG block 0 lines 4 to 7
JPEG block 1 lines 4 to 7
JPEG block n lines 4 to 7
255 191 127 63 0
C3L4 C2L4 C1L4 C0L4 word q
C3L5 C2L5 C1L5 C0L5 word q+1
C3L6 C2L6 C1L6 C0L6 word q+2
C3L7 C2L7 C1L7 C0L7 word q+3
Implies 4 x 64 bit writes to consecutive words in one DRAM row, for a single CDU access to DRAM
CX - Color X
LY - Line Y or 8 bytes of a line in a JPEG block

FIG. 139


Reset OR prst_n == 0
cdu_diu_wreq = 0
cdu_diu_wvalid = 0
rd_adv = 0
rd_adv_half_block = 0
reset
Go == 0
cdu_diu_wreq = 0
cdu_diu_wvalid = 0
rd_adv = 0
rd_adv_half_block = 0
idle
Go == 1
cdu_diu_wreq = 0
cdu_diu_wvalid = 0
rd_adv = 0
rd_adv_half_block = 0
req
line_store_ok_to_write == 1 AND
half_block_ok_to_read == 1
cdu_diu_wreq = 1
cdu_diu_wvalid = 0
rd_adv = 0
rd_adv_half_block = 0
ack
diu_cdu_wack == 1
cdu_diu_wreq = 0
cdu_diu_wvalid = 0
rd_adv = 1
rd_adv_half_block = 0
read
cdu_diu_wreq = 0
cdu_diu_wvalid = 1
rd_adv = 1
rd_adv_half_block = 0
write1
cdu_diu_wreq = 0
cdu_diu_wvalid = 1
rd_adv = 1
rd_adv_half_block = 0
write2
cdu_diu_wreq = 0
cdu_diu_wvalid = 1
rd_adv = 1
rd_adv_half_block = 1
write3
cdu_diu_wreq = 0
cdu_diu_wvalid = 1
rd_adv = 0
rd_adv_half_block = 0
write4
cdu_diu_wreq = 0
cdu_diu_wvalid = 0
rd_adv = 0
rd_adv_half_block = 0

FIG. 140


SoPEC #1
lead-in area
SoPEC #2
lead-in area
SoPEC #1
lead-out area
SoPEC #2
lead-out area
margin area
JPEG
block 0
JPEG
block 1
JPEG
block n-1
JPEG
block n
JPEG
block n+1
JPEG
block m-1
JPEG
block m
target page area
SoPEC #1 prints left
side of page
SoPEC #2 prints right
side of page

FIG. 141


DRAM Interface Unit
Contone Decoder Unit
diu_data
cfu_diu_rreq
diu_cfu_ack
diu_cfu_rvalid
cfu_diu_radr
cfu_cdu_rdadvline
cdu_cfu_linestore_rdy
diu_control
64
17
decompressed contone buffer
2 wr_buff, rd_buff
2 wr_en, rd_en
5 wr_sel[1:0], rd_sel[2:0]
Y-scaling control unit
32
y_scale_num
y_scale_denom
max_block
buff_start_adr
buff_end_adr
wr_adv
8
13
15
K Cb Cr Y
color space converter
cp3 cp2 cp1 cp0
YCrCb2RGB
invert_color_plane
configuration registers
16
3
hcu_line_length
x_scale_num
x_scale_denom
x_start_count
leadin_clip_num
leadout_clip_num
outbuff_ok_to_write
hcu_control
output double-buffer
X-scaling control unit
Conton FIFO Unit
cfu_hcu_c3data
cfu_hcu_c2data
cfu_hcu_c1data
cfu_hcu_c0data
cfu_hcu_avail
hcu_cfu_dotadv
data
control
Halftone/Compositor Unit
PEP Controller Unit

FIG. 142


DRAM
DRAM word p
DRAM word p+4
DRAM word p+4n
4 line store
JPEG block 0 lines 0 to 3
JPEG block 1 lines 0 to 3
JPEG block n lines 0 to 3
DRAM word q
DRAM word q+4
DRAM word q+4n
4 line store
JPEG block 0 lines 4 to 7
JPEG block 1 lines 4 to 7
JPEG block n lines 4 to 7
255 191 127 63 0
C3L0 C2L0 C1L0 C0L0 word p
C3L1 C2L1 C1L1 C0L1 word p+1
C3L2 C2L2 C1L2 C0L2 word p+2
C3L3 C2L3 C1L3 C0L3 word p+3
255 191 127 63 0
C3L4 C2L4 C1L4 C0L4 word q
C3L5 C2L5 C1L5 C0L5 word q+1
C3L6 C2L6 C1L6 C0L6 word q+2
C3L7 C2L7 C1L7 C0L7 word q+3
Implies one 256 bit read of a word in DRAM
CX - Color X
LY - Line Y or 8 bytes of a line in a JPEG block

FIG. 143


Reset OR prst_n == 0
cfu_diu_rreq = 0
wr_sel = 0
wr_adv_buff = 0
reset
Go == 0
cfu_diu_rreq = 0
wr_sel = 0
wr_adv_buff = 0
idle
Go == 1
cfu_diu_rreq = 0
wr_sel = 0
wr_adv_buff = 0
req
line8_ok_to_read AND
buff_ok_to_write
cfu_diu_rreq = 1
wr_sel = 0
wr_adv_buff = 0
ack
diu_cfu_rack == 1
cfu_diu_rreq = 0
wr_sel = 0
wr_adv_buff = 0
read1
diu_cfu_rvalid == 1
cfu_diu_rreq = 0
wr_sel = 0
wr_adv_buff = 0
read2
diu_cfu_rvalid == 1
cfu_diu_rreq = 0
wr_sel = 1
wr_adv_buff = 0
read3
diu_cfu_rvalid == 1
cfu_diu_rreq = 0
wr_sel = 2
wr_adv_buff = 0
read4
diu_cfu_rvalid == 1 AND
cfu_diu_rreq = 0
wr_sel = 3
wr_adv_buff = 1

FIG. 144



FIG. 145



FIG. 146


64
DRAM read
LBD
FIFO
DECODE
All FIFOs are 64 bytes (twice the DRAM data word width)
16
16
SFU
FIFO
next_line
FIFO
prev_line
64
DRAM write
64
DRAM read
FIFO
curr_line
1
HCU

FIG. 147


DRAM Interface Unit
data
readadr
control
64
17
lossless bi-level decoder unit
Stream Decoder
pass_through_dot_length
pass_through_enable
Register and Resets
prev_line_source
lines_remaining
line_length
2
15
command
delta
control
lbd_finishedband
End of Band Unit
control
15
a0
15
b1p
Command Controller
Next Edge Unit
1
lbd_sfu_pladvword
16
sfu_lbd_pldata
Previous Line Buffer
Spot FIFO Unit
a0
15
control
sfu_lbd_rfy
1
ldb_sfu_advline
Line Fill Unit
data
16
lbd_sfu_wdata
datavalid
wdatavalid
Next Line Buffer

FIG. 148


DRAM Interface Unit
readadr
control
data
64
Stream Decoder
17
state machine
64
FIFO >=9 Locations
CurrReadAdr
24
64
0
1
+1
24
24
64-bit Barrel Shift Register
shift
20···3
6···0
=
DecodeD
DecodeC
24
15
3
delta
command
SdAcc
SdValid
15
3
StartOfBandStore
EndOfBandStore
Command Controller

FIG. 149


next edge unit
neu_done
neu_state
b1p
horizontal_end
first_line_of_band
cc_state
sd_color
a0
first_flu_write
advance_horizontal
end of band unit
eob_cc
15
color
stream decoder
delta
15
delta
15
15
a0
15
command
3
command
ld
State Machine
SdAck
SdValid
command controller
go_lbd
sfu_rdy
line_length
prev_line_source
ignore_prev_line
end_of_line
sd_color
A0
line fill unit

FIG. 150


START
AWAIT_BUFF
PARSE
FINISH_LINE
PAUSE_CC
WAIT_FOR_RUNLENGTH
WAIT_FOR_NE
NEU_STATE!= NEU_RUNNING
NEU_STATE == NEU_RUNNING
current_line_pos == LINE_LENGTH
SDVALID == 0
SDVALID == 1
current_line_pos != prev_line_pos + delta
current_line_pos == prev_line_pos + delta
NEU_DONE == 0
NEU_DONE == 1
SDVALID == 0 OR SFU_LBD_RDY == 0
SDVALID == 0 OR SFU_LBD_RDY == 0

FIG. 151


SFU
sfu_lbd_pldata
16
lbd_sfu_pladvword
lbd_sfu_advline
buffer
prev_line_a
16
prev_line_b
16
Stream Decoder
delta
command
2
15
detect edge
sd_color
b1p
neu_done
15
Command Controller
control signals
plbuff_rdy
neu_state
line_length
first_flu_wr
radv_horiz
cc_state
a0
3
15
4
15
state machine
hold_sd_color
vminus_zero
Next Edge Unit
Line Fill Unit

FIG. 152


16
use_prev_line_a
16
use_prev_line_b
pl_buff_rdy
16
sfu_lbd_pldata
pl_buff_rdy_dly

FIG. 153


use_prev_line_a
15
0
use_prev_line_b
15
2
0
16
3
19
transition_wtob
transition_btow
19
19
color_neu
0
1
19
decode_b_ext & decode_b & FIRST_FLU_WRITE
19
19
end_frame
19
19
masked_data
encode_b_one_hot
19
encode_b_4bit
4
b1p

FIG. 154


NEU_START
CC_STATE == AWAIT_BUFF
NEU_FILL_BUFF
NEU has read 1st 4 frames from previous line
NEU_HOLD
NEU_RUNNING
NEU has read all the previous line
NEU_EMPTY

FIG. 155


SFU
lbd_sfu_wdata
16
lbd_sfu_wdatavalid
lbd_sfu_advline
line_fill_data
work_sfu_wdata
line_length
15
4
limit
lfu_state
color_sel_16bit_lf
16
16
command controller
eob_lfu
end_of_line
sd_color
horizontal_end
eob_cc
15
a0
State Machine
line fill unit
hold_sd_colon
vminus_zero
command
delta
Next Edge Unit
Stream Decoder

FIG. 156


LFU_START
LFU_NEW_REG
LFU_COMPLETE_REG
ao == LINE_LENGTH
ao != 0
frame completed
frame not completed
frame completed
frame not completed
ao == LINE_LENGTH

FIG. 157


high address
lbd_nextline_wr_adr
lbd_prevline_rd_adr
hcu_readline_rd_adr
hcu_startreadline_adr
low address
(a)
high address
lbd_nextline_wr_adr
hcu_readline_rd_adr
lbd_prevline_rd_adr
hcu_startreadline_adr
low address
(b)
Key:
Free buffer space
Filled buffer space accessed by LBD Interface FIFOs
Filled Buffer space read by HCU Read Line FIFO
Filled Buffer space read by both HCU Read Line FIFO and LBD Interface FIFOs

FIG. 158


HCU
hcu_sfu_advdot
1 sfu_hcu_sdata
sfu_hcu_avail
SFU
DIU
DIU Interface and Address Generator
Current Line FIFO
Previous Line FIFO
plf_rdy
nlf_rdy
Next Line FIFO
lbd_sfu_placword
sfu_lbd_pldata 16
lbd_sfu_advline
sfu_lbd_rdy
lbd_sfu_wdata 16
lbd_sfu_wdatavalid
lbd_sfu_advline
LBD

FIG. 159


PCU Interface
DIU Interface Address Generator Unit (DAG)
LBD
LBD Previous Line FIFO
LBD Next Line FIFO
HCU
HCU Read Line FIFO
SFU
sfu_go (to all sub-blocks)
hcu_num_dots
hcu_dram_words
lbd_dram_words
start_sfu_adr
end_sfu_adr
hcu_readline_rd_adr
hcu_startreadline_adr
lbd_nextline_wr_adr
lbd_prevline_rd_adr
xstart_count
xscale_num
xscale_denom
yscale_num
yscale_denom
pcu_rwn
pcu_sfu_sel
pcu_adr[5:2]
pcu_dataout[31:0]
sfu_pcu_datain[31:0]
sfu_pcu_rdy
sfu_diu_wreq
sfu_diu_wadr[21:5]
sfu_diu_data[63:0]
sfu_diu_wvalid
diu_sfu_wack
sfu_diu_rreq
sfu_diu_radr[21:5]
diu_sfu_data[63:0]
diu_sfu_rvalid
diu_sfu_rack
lbd_sfu_pladvword
sfu_lbd_pldata
lbd_sfu_advline
plf_diurreq
plf_diurack
plf_diurdata
plf_diurvalid
plf_diuidle
sfu_lbd_rdy
plf_rdy
nlf_rdy
lbd_sfu_wdata
lbd_sfu_wdatavalid
lbd_dram_words
nlf_diuwreq
nlf_diuwack
nlf_diuwdata
nlf_diuwvalid
hcu_sfu_advdot
sfu_hcu_sdata
sfu_hcu_avail
hrf_hcu_endofline
hrf_xadvance
hrf_diurreq
hrf_diurack
hrf_diurdata
hrf_diurvalid
hrf_diuidle

FIG. 160


plf_diurdata
64
write_adr
3
plf_diurreq
plf_diurack
plf_diurvalid
8 word
64-bit FIFO
write
read
write_en
read_adr
3
3
64
16
ZERO
FIFO control
logic
word_select
3
16
16
LBD
16
sfu_lbd_pldata
lbd_sfu_advline
lbd_dram_words8
plf_rdy

FIG. 161


pclk
plf_diurreq
plf_diurack
plf_diurvalid
plf_diurdata[63:0]
1
2
3
4

FIG. 162


sfu_go==0
reset==0
Idle
diuidle = 1
256-bits free in FIFO
Request
diurreq = 1, diuidle =0
diurack==1
Ack
diurreq = 0
diurvalid==1
Data0
diurvalid==1
Data1
diurvalid==1
Data2
diurvalid==1
Data3

FIG. 163


lbd_sfu_wdata
16
sfu_wdata_reg
16
16
en
word_select
8 word
64-bit FIFO
write
read
64
nlf_diuwdata
write_adr
write_en
bit_write
read_adr
3
3
FIFO control
logic
lbd_sfu_wdatavalid
lbd_sfu_advline
nlf_rdy
nlf_diuwreq
nlf_diuwack
nlf_diuwvalid

FIG. 164


pclk
nlf_diuwreq
nlf_diuwack
nlf_wdiudata[63:0]
1
2
3
4
nlf_diuwvalid

FIG. 165


sfu_go==0
reset==0
Idle
256-bits in FIFO
Request
diuwreq = 1
diurack==1
Data0
diuwvalid=1
Data1
diuwvalid=1
Data2
diuwvalid=1
Data3
diuwvalid=1

FIG. 166


Write from LBD to SFU (NextLineFifo)
pclk
sfu_lbd_rdy
lbd_sfu_wdatavalid
FIFO free words Level
FIFO read enable
0x2
0x1
0x0
0x1
0x2
0x1
0x0
1
2
3
4
5
6
7
8
9
10

FIG. 167


Read from SFU to LBD (PreviousLineFifo)
pclk
sfu_lbd_rdy
lbd_sfu_pladvword
FIFO fill Level
sfu_lbd_pldata
FIFO write enable
0x3
0x2
0x1
0x2
0x3
0x2
0x1
D0
D1
D2
D3
1
2
3
4
5
6
7
8
9
10

FIG. 168


hrf_diurdata
64
8 word
64-bit FIFO
write
read
write_adr
write_en
read_adr
3
3
64
6
bit_select
FIFO control
logic
hrf_diurreq
hrf_diurack
hrf_diurvalid
sfu_hcu_avail
hcu_sfu_advdot
hcu_num_dots
16
hrf_xadvance
hrf_hcu_endofline
HCU
1
1
sfu_hcu_sdata

FIG. 169



FIG. 170



FIG. 171



FIG. 172



FIG. 173



FIG. 174



FIG. 175


start of next hcu line in DRAM =
hcu_startreadline_adr + lbd_dram_words
When DRAM reads for line
are complete advance to next
line or return to start of current line
according to Y-scaling.
Y-scale
logic
hrf_yadvance
hrf_hcu_endofline
hcu_sfu_advdot
X-scale
logic
hrf_xadvance
1
hcu_readline_rd_adr
hcu_startreadline_adr
256 bits
Number of DRAM reads for the line
determined by end of HCU line
according to X-scaling.
read from DRAM
Advance
dot count
from HCU
256 bits
256 bits
1
sfu_hcu_sdata
HCUReadLineFifo
hcu_sfu_advdot
DRAM

FIG. 176



FIG. 177



FIG. 178



(a) Netpage tag background pattern

(b) Netpage tag showing data area

FIG. 179



FIG. 180



FIG. 181



FIG. 182


dot direction
Tag height
Tag width
tag within tag's bounding box
Dot inter-tag gap
Line inter-tag gap
Dot inter-tag gap
tag within tag's bounding box
tag within tag's bounding box
tag within tag's bounding box
Start Position
AltTagLine Position
line direction

FIG. 183


Tag Format Structure
tag line structure 0
tag line structure 1
tag line structure 2
...
tag line structure 6
tag line structure 7
tag line structure 8
...
tag line structure n
TagHeight tag line structures
tag line structure
table A
(384 entries x 2-bits)
(768 bits)
table B
(32 entries x 9-bits)
(288 bits)
table C
(2 entries x 5-bits)
(10 bits)
reserved and
unused
(214 bits)
1280 bits (5 x 256-bit words)

FIG. 184



always 1 (background)	always 1 (background)	always 1 (background)
data bit 0	data bit 1	data bit 2
data bit 4	data bit 5	data bit 3

FIG. 185



FIG. 186


DRAM interface
17
64
17
tag encoder unit
readAdr
control
dataIn
control
readAdr
tagaltsense
lastdotIntag
advtagline
tfsvalid
TFS interface
etdRdAdr0
etdRdAdr1
9
9
tag data interface
lastDotInTag1
tdValid
dotposvalid
8
2
2
tagIsPrinted
1
1
1
etd0
etd1
tagDotNum
taEven
taEOdd
1 bit 1
1 bit 0
1 bit 1
1 bit 0
tagMaxDotpairs
a
a-b
b
dotPos
lastdotintag
lastdotintag1
dotposvalid
tag dot 1
tag dot 0
state machine
dotsInTag
Logic
okToWrite
currTagPlaneAdr
14
2 (lo bits)
tpwe
3 × 2-bit shift register
6 (lo bits)
te_finishedband
tfu_te_oktowrite
te_tfu_wdatavalid
8 te_tfu_wdata
Tag Fifo Unit
PCU

FIG. 187


Tag Encoder
Top Level FSM
+ PCU + Comb
Logic for Muxing
etc.
Tag Data Interface
Raw Tag Data
Interface
Reed Solomon
Encoder
2D Decoder
Encoded Tag Data Interface
encoded
fixed tag
data
encoded
variable tag
data
Tag Format Structure (TFS)
Table A
Reg o/p
Table C
Table B
Reg o/p

FIG. 188


te_pcu_datain[31:0]
te_pcu_rdy
top level
read decode
sub-block
write decode
write decode
control
pcu_dataout[31:0]

FIG. 189


dotsintag2
tdvalid2
tfsvalid2
tfu_ok_write2
dotsintag1
tdvalid1
tfsvalid1
tfu_ok_write1
lineintag1
dotsintag
tdvalid
tfsvalid
tfu_ok_write
lineintag_temp
pclk

FIG. 191



FIG. 190



FIG. 192



FIG. 193



FIG. 194



FIG. 195



FIG. 196


DRAM interface
17
64
tag data interface
control
readAdr
dataIn
te_finishedband
raw tag data interface FSM
1
rtdAvail
rtdRd
state machine
1
tdValid
lastDotInTag
lastDotInTag1
rtd
64
tdwe
2
tagData (2 × 64 bits)
20
20
20
28
28
20
20
20
28
28
1
b0-b19
b40-b59
b80-b99
b0-b27
b56-b83
b20-b39
b60-b79
b100-b119
b28-b55
b84-b111
b120
etdAdvTag
level1_mux
0 1 2
0 1
0 1 2
0 1
tagIsPrinted
1
tagIsPrinted
20
28
20
28
level2_mux
0 1
0 1
28
28
level3_mux
4
4
selLow
selLow
RScontrol
dataRedun
RS0
dec
RS1
dec
4
4
4
4
dataRedun
decode2DEn
level4_mux
0 1
0 1
4
4
8
etdRdAdr0
etdRdAdr1
9
9
encoded tag data interface
1
1
etd0
etd1
etdAdvTag
etdwe
etdWrAdr
6

FIG. 197


ENCODED TAG DATA INTERFACE
-Encoded fixed data can be up to 120 bits long
-Use 2 buffers to allow for 2 simultaneously READs in one cycle.
-These stores hold the fixed tag data for 1 tag.
-Total memory = 120x2 = 240 bits
RAW TAG DATA INTERFACE
8*64
WRITE
FIFO
READ
2*64
TAG DATA REGISTER
64
0
1
REED SOLOMON/ DECODE 2D
REED SOLOMON GF(2^4) ENCODER
2D DEC
REED SOLOMON GF(2^4) ENCODER
2D DEC
FIXED DATA
one tag
8
WRITE
15
READ
15
READ
VARIABLE DATA
one tag
8
WRITE
15
READ
15
READ
8
WRITE
15
READ
15
READ
-The requested tag is READ into this 128-bit buffer.
-This buffer can be updated up to 163 times/line.
-Each tag will be loaded at least 126 times.
-Have to be able to read one tag's data from the Raw Tag Data Interface, RS encode and store it in the Encoded Tag Data Interface in 63 cycles or less.
-min dot/tag 126 (specified)
-max dots/line = 1600x12.8 = 20480
-max tags/line = 20480/126 = 163
-max variable data/tag = 120
-max amount of tag data/line = 120 x 164
-Split the 120 tag data bits into 2x64-bits (8 spare bits)
-Max memory needed for 1 line of tag data = 2x64x164 = 656x32
-Divide this in half to allow for simultaneous READ/WRITE
-Once all this data is loaded it will be valid for at least 126 lines.
-From the specification, we must be able to process 2 dots/cycle.
-126 lines contains 20480x126 = 2580480 dots.
-Therefore the data will be updated at most every 1290240 cycles.
-Total memory = 164x2x64 = 20992-bits
-The store uses 9-bit addressing. Bit-9 indicates which buffer.
-Once printing has started each half buffer has 1/2 a line in which to be loaded
i.e. for a 12,8 inch line it has 10240 dots or 5120 cycles
for an 8 inch line it has 6400 dots or 3200 cycles
-Encoded variable data can be up to 360 bits long
-Use 2 buffers to allow for 2 simultaneously READs in one cycle.
-Use 2 buffers to allow for simultaneously READ/WRITE
-Total memory = 360x2x2 = 1280 bits
-Min tag width = 126 dots
so the fastest that 1 tag can be read = 126/2 = 63 cycles

FIG. 198


raw tag data Interface
DRAM interface
17
readAdr
control
rtd state machine
te_finishedband
fifo_wr_en
rtdbuf[63:0]
(2* rtdbuf data registered in Tag Data Reg)
raw tag data FIFO (8 x 64-bits)
diu_data[63:0]
wrptr
rtd_fifo_wr_en
rdptr
pclk
rtdbuf[63:0]
rtdrd
(rtdrd generated in TD FSM)
rtdavail
0
1
>0
rdptr
wr_rd_counter
+1
D
Q
EN
pclk
rtdrd
wrptr
rtd_fifo_wr_en
Logic
count_ctrl
fifo_wr_en
diu_td_rvalid

FIG. 199



FIG. 200



FIG. 201


idle
fixed_data
bypass_to_edti
rs_15_5
rs_15_7
decode_2d_15_5
decode_2d_15_7
etd_buf_switch
read_tag_data
load_tag_data
variabledatapresent == 0
go ==1 AND donefixed == 0
encodefixed == 1 AND dataredun == 0 AND decode2den == 1
encodefixed == 1 AND dataredun == 1 AND decode2den == 1
encodefixed == 1 AND dataredun == 0 AND decode2den == 0
encodefixed == 1 AND dataredun == 1 AND decode2den == 0
encodefixed== 0
idle
variabledatapresent == 1
dataredun == 0 AND decode2den == 1
dataredun == 0 AND decode2den== 0
dataredun == 1 AND decode2den == 0
dataredun == 1 AND decode2den== 1

FIG. 202


DRAM
tdi_diu_adr
tdi_diu_adr+1
tdi_diu_adr+2
tdi_diu_adr+3
curr_write_adr/curr_read_adr
curr_write_adr+1/curr_read_adr+1
halftagline0/1
TE_tagdata(127:0)
TE_tagdata(119:0)
TE_tagdata(119:0)
wradr(5:0)
RS0
RS1
d0 to d9 are encoded and stored during cycles N to N+14
d10 to d19 are encoded and stored during cycles N+15 to N+29
d20 to d29 are encoded and stored during cycles N+30 to N+44
codeword 1
codeword 0
codeword 3
codeword 2
codeword 5
codeword 4

FIG. 203


wradr(5:0)
3E p19 p9
3D p18 p8
3C p17 p7
3B p16 p6
3A p15 p5
39 p14 p4
38 p13 p3
37 p12 p2
36 p11 p1
35 p10 p0
34 d9 d4
33 d8 d3
32 d7 d2
31 d6 d1
30 d5 d0
codeword 7
codeword 6
p9 p8 p7 p6 p5 p4 p3 p2 p1 p0 d4 d3 d2 d1 d0
p19 p18 p17 p16 p15 p14 p13 p12 p11 p10 d9 d8 d7 d6 d5
RS0
RS1
TE_tagdata(119:0)
d4 d3 d2 d1 d0
d9 d8 d7 d6 d5
d0 to d9 are encoded and stored
during cycles N to N+14

FIG. 204


wradr(5:0)
3E
3D
3C
3B
3A
39
38
37
36
35
34
33
32
31
30
d_{29} d_{24}
d_{28} d_{23}
d_{27} d_{22}
d_{26} d_{21}
d_{25} d_{20}
d_{19} d_{14}
d_{18} d_{13}
d_{17} d_{12}
d_{16} d_{11}
d_{15} d_{10}
d_9 d_4
d_8 d_3
d_7 d_2
d_6 d_1
d_5 d_0
codeword 7
codeword 6
TE_tagdata(119:0)
d_4 d_3 d_2 d_1 d_0
d_9 d_8 d_7 d_6 d_5
d_{14} d_{13} d_{12} d_{11} d_{10}
d_{19} d_{18} d_{17} d_{16} d_{15}
d_{24} d_{23} d_{22} d_{21} d_{20}
d_{29} d_{28} d_{27} d_{26} d_{25}
d0 to d29 are stored
during cycles N to N+14

FIG. 205


DRAM
tdi_diu_adr
tdi_diu_adr+1
tdi_diu_adr+2
tdi_diu_adr+3
31 29 . . . . 1 0
63 62 . . . . 33 32
95 94 . . . . 65 64
127 126. . . . 97 96
curr_write_adr/curr_read_adr
curr_write_adr+1/curr_read_adr+1
halftagline0/1
63 62 . . . . 1 0
127 126. . . . 65 64
TE_tagdata(127:0)
63 62 . . . . 1 0
127 126. . . . 65 64
TE_tagdata(111:0)
27 26 . . . . 1 0
55 54 . . . . 29 28
83 82 . . . . 57 56
111 110 . . . . 85 84
TE_tagdata(111:0)
d6 d5 d4 d3 d2 d2 d0
wradr(5:0)
TE_tagdata(111:0)
d6 d5 d4 d3 d2 d2 d0
d13 d12 d11 d10 d9 d8 d7
RS0
RS1
p7 p6 p5 p4 p3 p2 p1 p0 d6 d5 d4 d3 d2 d1 d0
p15 p14 p13 p12 p11 p10 p9 p8 d13 d12 d11 d10 d9 d8 d7
d0 to d13 are encoded and stored
during cycles N to N+14
0E p15 p7
0D p14 p6
0C p13 p5
0B p12 p4
0A p11 p3
09 p10 p2
08 p9 p1
07 p8 p0
06 d13 d6
05 d12 d5
04 d11 d4
03 d10 d3
02 d9 d2
01 d8 d1
00 d7 d0
codeword 1
codeword 0
wradr(5:0)
TE_tagdata(111:0)
d20 d19 d18 d17 d16 d15 d14
d27 d26 d25 d24 d23 d22 d21
RS0
RS1
p23 p22 p21 p20 p19 p18 p17 p16 d20 d19 d18 d17 d16 d15 d14
p31 p30 p29 p28 p27 p26 p25 p24 d27 d26 d25 d24 d23 d22 d21
d14 to d27 are encoded and stored
during cycles N+15 to N+29
1E p31 p23
1D p30 p22
1C p29 p21
1B p28 p20
1A p27 p19
19 p26 p18
18 p25 p17
17 p24 p16
16 d27 d20
15 d26 d19
14 d25 d18
13 d24 d17
12 d23 d16
11 d22 d15
10 d21 d14
codeword 3
codeword 2

FIG. 206


wradr(5:0)
3E
3D
3C
3B
3A
39
38
37
36
35
34
33
32
31
30
codeword 7
codeword 6
RS0
RS1
TE_tagdata(111:0)
d0 to d13 are encoded and stored during cycles N to N+14

FIG. 207


halftagline0/1
63 62 . . . . 1 0
127 126. . . . 65 64
TE_tagdata(127:0)
63 62 . . . . 1 0
127 126. . . . 65 64
TE_tagdata(119:0)
19 18 . . . . 1 0
39 38 . . . . 21 20
59 58 . . . . 41 40
79 78 . . . . 61 60
99 98 . . . . 81 80
119 118 . . 101 100
TE_tagdata(119:0)
h4 l4 h3 l3 h2 l2 h1 l1 h0 l0
hx = upper 2-bits of symbol x
lx = lower 2-bits of symbol x
Hx = hx after 2D decoding (4-bits long)
Lx = lx after 2D decoding (4-bits long)
2D Decoding
hx/lx
Hx/Lx
0 0
0 0 0 1
0 1
0 0 1 0
1 0
0 1 0 0
1 1
1 0 0 0
wradr(5:0)
TE_tagdata(119:0)
h4 l4 h3 l3 h2 l2 h1 l1 h0 l0
h9 l9 h8 l8 h7 l7 h6 l6 h5 l5
DEC
DEC
X = dont care
0E X X
0D X X
0C X X
0B X X
0A X X
09 H9 H4
08 H8 H3
07 H7 H2
06 H6 H1
05 H5 H0
04 L9 L4
03 L8 L3
02 L7 L2
01 L6 L1
00 L5 L0
codeword 1
codeword 0
X = dont care
wradr(5:0)
h14 l14 h13 l13 h12 l12 h11 l11 h10 l10
h19 l19 h18 l18 h17 l17 h16 l16 h15 l15
DEC
DEC
1E X X
1D X X
1C X X
1B X X
1A X X
19 H19 H14
18 H18 H13
17 H17 H12
16 H16 H11
15 H15 H10
14 L19 L14
13 L18 L13
12 L17 L12
11 L16 L11
10 L15 L10
codeword 3
codeword 2
wradr(5:0)
h24 l24 h23 l23 h22 l22 h21 l21 h20 l20
h29 l29 h28 l28 h27 l27 h26 l26 h25 l25
DEC
DEC
X = dont care
2E X X
2D X X
2C X X
2B X X
2A X X
29 H29 H24
28 H28 H23
27 H27 H22
26 H26 H21
25 H25 H20
24 L29 L24
23 L28 L23
22 L27 L22
21 L26 L21
20 L25 L20
codeword 5
codeword 4

FIG. 208

FIG. 209



FIG. 210


control_7
mux1
control_5
mux2
control_7
control_5
TE_dataredun
mux3
codeword symbols
mux4
rs_data_out(3:0)
rs_data_in(3:0)
$(d_6,d_5,)d_4,d_3,d_2,d_1,d_0$
h_0 h_1 h_2 h_3 h_4 h_5 h_6 h_7
g_0 g_1 g_2 g_3 g_4 g_5 g_6 g_7 g_8 g_9
denotes an multiplier that multiplies Galois Field elements
denotes an adder that adds Galois Field elements

FIG. 211


clk
rs_data_in[3:0]
rs_data_out[3:0]
rs_counter
TE_dataredun
control_5
control_7

FIG. 212


clk
rs_data_in[3:0]
rs_data_out[3:0]
rs_counter
TE_dataredun
control_5
control_7

FIG. 213



FIG. 214



FIG. 215


control_7
h0 (α6) h1 (α11) h2 (α5) h3 (α13) h4 (α2) h5 (α4) h6 (α2) h7 (α14)
control_5
g0 (α10) g1 (α) g2 (α6) g3 (α) g4 (α2) g5 (α14) g6 (α6) g7 (α9) g8 (α3) g9 (α2)
⊕, + exclusive OR gate
4-bit shift register
rs_data_in(3:0)
(d6,d5,) d4,d3,d2,d1,d0
rs_data_out(3:0)
e0,e1,...,e13,e14

FIG. 216


encoded tag data interface
dataIn
rdAdr0
etdwe
rdAdr1
wrAdr
advTag
etd0
etd1
encoded fixed tag data
encoded variable tag data
reord
reord
dataIn
out0
out1
rdAdr0
rdAdr1
wrAdr
eftdwe
evtdwe
advTag
2 (hi bits)
4 (low bits)
7 (low bits)
2 (hi bits)
2 (hi bits)

FIG. 217


encoded fixed tag data interface
out0
out1
1
8
(15 × 8 bit)
adr
dataIn
we
3 (lo bits)
4 (hi bits)
0
1
4
7
rdAdr0
wrAdr
eftwe
8
dataIn
rdAdr1

FIG. 218


encoded variable tag data interface
advTag
we
wrsb0
(1 bit)
rdAdr0
rdAdr1
wrAdr
dataIn
evtdwe
variable
tag data
sub buffer 0
variable
tag data
sub buffer 1
out0
out1

FIG. 219


encoded variable tag data sub buffer
out0
out1
1
8
(3 × 15 × 8 bit)
adr
dataIn
we
3 (lo bits)
6
6 (hi)
9
6
rdAdr0
wrAdr
we
8
dataIn
9
rdAdr1
6 (hi bits)
3 (lo bits)
0
1

FIG. 220


TE_tfsstartadr
TLS 0
TLS 1
TLS 2
TLS n
TE_tfsendadr
Tag Format Structure
The number of dot lines
in a Tag = n+1
i.e. TagHeight = n+1
0
31
Table A
24 x 32-bits=768-bits
(384 entries x 2-bits)
0
1
23
24
Table B
9 x 32-bits=288-bits
(32 entries x 9-bits)
32
33
39
214-bits reserved and unused
0
9
Table C
10-bits
(2 entries x 5-bits)

FIG. 221


top_go == 0
idle
top_go == 1
diu_access
diu_tfs_rack == 1
tls_load
read_num == 16
tls_update
read_num == 31
tls_next
tfs_valid == 0
tls_tfsvalid_set
tfsvalid == 1 AND
top_advtagline == 1

FIG. 222


TFS interface
tawe
tcwe
table A interface
table C interface
table B interface
2 taOdd
2 taEven
in1
in0
tbRdAdr1
tbRdAdr0
tbwe
taOdd
taEven
dotsPosValid
etdRdAdr0
etdRdAdr1
2
2
5
5
9
9
taRdAdr
advTFSLine
10 (bits32-41)
state machine
8
64
17
1
tagDotNum
dataIn
readAdr
control
tfsValid
tagAltSense
lastDotInTag
advTagLine
DRAM interface

FIG. 223


Table A interface
AdrGen
wrta0
taWrAdr
advTFSLine
tawe
taRdAdr
dataIn
adr
dataIn
we
16 x 64-bits table A (0)
16 x 64-bits table A (1)
ta_dot0_1cyclelater
ta_dot1_1cyclelater
2 (bits 1&0)
2 (bits 3&2)
taEven
taOdd

FIG. 224


table A
address gen
wrta0
taWrAdr
wrta0
(1 bit)
taWrAdr
(4 bits)
+1
1
4
4
0
1
0
we
we
advTFSLine
tawe

FIG. 225


tbRdAdr1
tbRdAdr0
table C
Interface
adr1sel
AdrGen
adrSel
in1
in0
2
2
5
5
5
+2
+1
0
1
0
lastDotInTag
dataIn
10
10
table C
(10 bits)
we
tcwe
1
5
1
0
5
5
adr (5 bits)
we
tagAltSense
advTFSLine
dotPosValid

FIG. 226


table B
interface
tfsi_adr0
tfsi_adr1
9
32 × 9-bits
table subB (0)
32 × 9-bits
table subB (1)
adr0
adr1
dataIn
we
5
10
AdrGen
tbwradr
tbwradr
tsbwe
wrtb0
288-bit
table B
temp reg
tbRdAdr0
tbRdAdr1
tbwe
advTFSLine
read_num
(from TFS FSM)
dataIn
pclk
64

FIG. 227



FIG. 228



FIG. 229


tag FIFO unit interface
tdata
control
spot FIFO unit interface
sdata
control
contone FIFO unit interface
8
c3data
8
c2data
8
c1data
8
c0data
control
Halftoner / Compositor Unit
6
dot
control
dead nozzle compensator
control
17
radr
64
data
DRAM interface unit

FIG. 230


Contone FIFO Unit
Spot FIFO Unit
Tag FIFO Unit
cfu_hcu_avail
hcu_cfu_advdot
cfu_hcu_c0data
cfu_hcu_c1data
cfu_hcu_c2data
cfu_hcu_c3data
sfu_hcu_avail
hcu_sfu_advdot
sfu_hcu_sdata
tfu_hcu_avail
hcu_tfu_advdot
tfu_hcu_tdata
Halftoner / Compositor Unit
contone dotgen
spot dotgen
tagplane dotgen
cp_avail
cp0
cp1
cp2
cp3
s_avail
s
tp_avail
tp
cp[0-3]_dither_val
in_target_page
advdot
in_target_tag_page
cp_avail, s_avail, tp_avail
cp[0-3]_constant
s_constant
tp_constant
io_mapping
dot reorg 0
dot reorg 1
dot reorg 2
dot reorg 3
dot reorg 4
dot reorg 5
in_page
config registers
margins
DM indices
tm/avail_mask
max_dot
DM addresses
dither_constant
double_line_buf
control unit
output_buff_full
wr_advdot
output buffer
control
data
hcu_ciu_rreq
diu_hcu_rack
hcu_diu_radr
diu_hcu_rvalid
diu_data
hcu_dnc_avail
dnc_hcu_ready
hcu_dnc_data
PCU
DRAM Interface Unit
Dead Nozzle Compensator

FIG. 231


wr_advdot
advdot
max_dot
hcu_diu_rreq
diu_hcu_rack
hcu_diu_radr
diu_hcu_rvalid
diu_data
dither matrix table interface
determine advdot
position unit
contone spot margin unit
tag margin unit
dm_avail
advline
dm_advline
dm_read_enable
double_line_buf
cp0_dither_val
cp1_dither_val
cp2_dither_val
cp3_dither_val
dither_constant
start_dm_adr
end_dm_adr
line_increment
DM indices
contone margins
page_margin_y
tag margins
curr_pos
curr_line
after_top_margin
in_target_page
in_page
after_tag_top_margin
in_tag_target_page
output_buffi full
cp_avail, s_avail, tp_avail
avail_mask, tm_mask
in_target_page
in_page
in_tag_target_page

FIG. 232


advdot unit
dm_read_enable
advdot
wr_advdot
tm_mask[0]
in_target_page
avail_mask[0]
dm_avail
after_top_margin
tm_mask[1]
avail_mask[1]
in_target_page
cp_avail
s_avail
tm_mask[2]
avail_mask[2]
after_tag_top_margin
tm_mask[3]
avail_mask[3]
in_tag_target_page
tp_avail
output_buff_full
in_page
Go
0
1

FIG. 233


target top margin
target page
printable page area
(physical page)
target left margin
target right margin
target bottom margin

FIG. 234


margin unit
curr_pos
curr_line
top_margin
bottom_margin
page_margin_y
right_margin
left_margin
a<b
a>=b
a>=b
a<b
a<b
in_page
in_target_page
after_top_margin
16
32
1
1
1
1
1
16
16
32
32
32

FIG. 235


DIU
hcu_diu_radr
diu_hcu_rack
hcu_diu_rreq
diu_hcu_rvalid
diu_data
17
64
dither matrix table interface
state machine
buff_full
wr_adr
5
dither matrix buffer unit
read address generator
rd_adr_c0
rd_adr_c1
rd_adr_c2
rd_adr_c2
8
start_dm_adr
end_dm_adr
line_increment
dm_read_enable
dither_constant
17
5
8
dm_advline
advline
advdot
dm_init_index_c[0-3]
dm_lwr_index_c[0-3]
dm_upr_index_c[0-3]
double_line_buf
dm_avail
cp0_dither_val
cp1_dither_val
cp2_dither_val
cp3_dither_val

FIG. 236


line 0
line 1
line 2
line 3
line 4
line 5
line 6
line 7
start_dm_adr
end_dm_adr
0
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
line_increment = 3
double_line_buf = 0

FIG. 237


Reset OR prst_n == 0
hcu_diu_rreq = 0
hcu_diu_radr = 0
access_count = 0
wr_adr = 0
reset
idle
Go == 0
hcu_diu_rreq = 0
hcu_diu_radr = hcu_diu_radr
access_count = access_count
wr_adr = wr_adr
Go == 1 AND
dm_read_enable == 1
hcu_diu_rreq = 0
hcu_diu_radr = start_dm_adr
line_start_adr = start_dm_adr
access_count = 0
wr_adr = 0
req
buff_full == 0
hcu_diu_rreq = 1
hcu_diu_radr = hcu_diu_radr
access_count = access_count
wr_adr = wr_adr
ack
diu_hcu_rack == 1
hcu_diu_rreq = 0
hcu_diu_radr = hcu_diu_radr
access_count = access_count
wr_adr = wr_adr
read1
diu_hcu_rvalid == 1 AND
access_count == 3/7 AND
hcu_diu_radr != end_dm_adr
hcu_diu_rreq = 0
hcu_diu_radr = line_start_adr +
line_increment
line_start_adr = line_start_adr +
line_increment
access_count = 0
wr_adr++
diu_hcu_rvalid == 1 AND
access_count != 3/7 AND
hcu_diu_radr != end_dm_adr
hcu_diu_rreq = 0
hcu_diu_radr = hcu_diu_radr + 1
access_count ++
wr_adr ++
diu_hcu_rvalid == 1
hcu_diu_rreq = 0
hcu_diu_radr = hcu_diu_radr
access_count = access_count
wr_adr ++
diu_hcu_rvalid == 1 AND
hcu_diu_radr == end_dm_adr
hcu_diu_rreq = 0
hcu_diu_radr = start_dm_adr
line_start_adr = start_dm_adr
access_count = 0
wr_adr++
read2
diu_hcu_rvalid == 1
hcu_diu_rreq = 0
hcu_diu_radr = hcu_diu_radr
access_count = access_count
wr_adr ++
read3
diu_hcu_rvalid == 1
hcu_diu_rreq = 0
hcu_diu_radr = hcu_diu_radr
access_count = access_count
wr_adr ++
read4

FIG. 238


contone dotgen unit
advdot
avail_mask[1]
in_target_page
cp0 dot
cp0_dither_val
cp1 dot
cp1_dither_val
cp2 dot
cp2_dither_val
cp3 dot
cp3_dither_val
cp[0-3]_constant
cp_avail
dither unit 0
dither unit 1
dither unit 2
dither unit 3
cp0_constant
cp1_constant
cp2_constant
cp3_constant
8
32
hcu_cfu_advdot
cfu_hcu_c0data
cfu_hcu_c1data
cfu_hcu_c2data
cfu_hcu_c3data
cfu_hcu_avail
Contone FIFO Unit

FIG. 239



FIG. 240


pclk
dnc_hcu_ready
hcu_dnc_data
hcu_dnc_avail
readdot
D1
D2
D3
D4
D5
D6
D7
D8
D9
DNC
Capture FF
6
en
dnc_newdot
Logic
hcu_dnc_data
dnc_hcu_ready
hcu_dnc_avail
HCU
Output Buffer
6
readdot
Readptr Logic
Out buffer fill level (not empty)
Logic

FIG. 241


pclk
hcu_sfu_advdot
sfu_hcu_sdata
sfu_hcu_avail
captured data in HCU
D1
D2
D3
D4
D5
D6
D7
D8
D9
D10
D11

FIG. 242


HCU
SFU
Logic
advdot
curr_pos,curr_line
AvailMask, TMMask
sfu_hcu_sdata_ff
1
en
sfu_hcu_sdata
sfu_hcu_advdot
hcu_sfu_avail
Logic

FIG. 243



FIG. 244



FIG. 245



FIG. 246


DRAM Interface Unit
dnc_diu_rreq
dnc_dwu_radr
diu_dnc_rack
diu_dnc_rvalid
diu_data
17
64
HCU
hcu_dnc_data
hcu_dnc_avail
dnc_hcu_ready
6
ink replacement unit
iru_avail
iru_data
6
iru_dn_mask
6
edu_ready
error diffusion unit
36
17
17
6
plane[5-0]_replace_pattern
dn_table_start_adr
dn_table_end_adr
diffuse_enable
max_dot
16
edu_dn_mask
edu_data
6
6
configuration registers
fixative_mask1
6
fixative_mask2
6
fixative correction unit
7
32
32
Dead Nozzle Compensator
6
pcu_dnc_sel
pcu_rwn
pcu_adr
pcu_dataout
dnc_pcu_rdy
dnc_pcu_datain
dnc_dwu_data
dnc_dwu_avail
dwu_dnc_ready
PEP Controller Unit
Dotline Writer Unit

FIG. 247


diu_data
64
dnc_diu_rreq
diu_dnc_rack
dnc_diu_radr
17
diu_dnc_rvalid
hcu_dnc_avail
dnc_hcu_ready
dead nozzle FIFO
2
rd_en, wr_en
3
fifo_wr_adr
5
fifo_rd_adr
control unit
17
dn_table_start_adr
17
dn_table_end_adr
iru_avail
edu_ready
16
preload
GenMask unit
rd_adv
dotadv
6
iru_dn_mask
dn_mask
6
replace unit
6
iru_data
hcu_dnc_data
6
diffuse_enable
6
36
plane[5-0]_replace_pattern

FIG. 248


Reset OR prst_n == 0
dn_table_rreq = 0
dn_table_radr = 0
reset
Go == 0
dn_table_rreq = 0
idle
Go == 1
dn_table_rreq = 0
dn_table_radr = dn_table_start_adr
req
fifo_contents <= (FifoSize - 4)
dn_table_rreq = 1
dn_table_radr = dn_table_radr
dn_table_radr != dn_table_end_adr
AND rd_count = 3
dn_table_rreq = 0
dn_table_radr ++
ack
dn_table_radr == dn_table_end_adr
AND rd_count = 3
dn_table_rreq = 0
dn_table_radr = dn_table_start_adr
diu_dnc_rack == 1
dn_table_rreq = 0
dn_table_radr = dn_table_radr
read

FIG. 249


plane0_replace_pattern
plane1_replace_pattern
plane2_replace_pattern
plane3_replace_pattern
plane4_replace_pattern
plane5_replace_pattern
dn_mask
b0
b1
b2
b3
b4
b5
diffuse_enable
hcu_dnc_data
iru_data
6

FIG. 250


edu_dn_mask
edu_data
random_seed
32
6
6
random bit generator
diffuse unit
advdot
16
6
6
advance dot unit
max_dot
iru_data
iru_dn_mask
iru_avail
dnc_dwu_avail
dwu_dnc_ready
edu_ready

FIG. 251



FIG. 252



FIG. 253



Note: Paper passes under printhead

FIG. 254


Encountered Nozzle Row Order
Nozzles
Paper
Print Line No:
Paper Flow
Ink Layers
D1
D2
Color 0
Color 1
Color 2
Color 3
Color 4
Color 5
O
E
0
1
2
3
4
5
6
7
8
9
10
11
55
50
45
40
35
30
25
20
15
10
5
0

FIG. 255


Even R w Encountered First
Color 5, Odd FIFO
Color 5, Even FIFO
Color 4, Odd FIFO
Color 4, Even FIFO
Color 3, Odd FIFO
Color 3, Even FIFO
Color 2, Odd FIFO
Color 2, Even FIFO
Color 1, Odd FIFO
Color 1, Even FIFO
Color 0, Odd FIFO
Color 0, Even FIFO
N Extra line store
D1
D2
DWU Write Side
LLU Read Side
Odd R w Encountered First
Color 5, Odd FIFO
Color 5, Even FIFO
Color 4, Odd FIFO
Color 4, Even FIFO
Color 3, Odd FIFO
Color 3, Even FIFO
Color 2, Odd FIFO
Color 2, Even FIFO
Color 1, Odd FIFO
Color 1, Even FIFO
Color 0, Odd FIFO
Color 0, Even FIFO
N Extra line store
D1
D2
DWU Write Side
LLU Read Side

FIG. 256



FIG. 257



FIG. 258


x1.5 Buffering
x2 Buffering
128 bits
write pt
read pt
FIFO empty writing begins
256 bits full, DRAM request issued
Variable cycles later DRAM request granted
256 bits transferred
256 bits full, DRAM request issued again
Variable cycles later DRAM request granted
256 bits transferred
Process repeated over one line
Final 256 bits full, DRAM request issued
Variable cycles later DRAM final request
granted, 256 bits transferred

FIG. 259



FIG. 260



FIG. 261


Decreasing Sense Colors
DRAM
ColorLineInc (words)
Dot Line 0
Dot Line 1
Dot Line 2
Dot Line N-2
Dot Line N-1
Dot Line N
ColorBaseAdr (words)
MaxWriteAhead (Lines)
ColorFifoSize = N lines
Increasing Sense Colors
DRAM
ColorLineInc (words)
Dot Line 0
Dot Line 1
Dot Line 2
Dot Line N-2
Dot Line N-1
Dot Line N
ColorBaseAdr (words)

FIG. 262


DNC
DRAM Interface Unit
dnc_dwu_data
dnc_dwu_avail
dwu_dnc_ready
6
17
64
dwu_diu_wadr
dwu_diu_wvalid
dwu_diu_data
dwu_diu_wreq
diu_dwu_wack
dwu_dnc_ready
Data skew
dwu_ready
zero_fill
dot_data
data_valid
6
x 12
wr_bit
2x64
wr_dot_data
2x6
wr_en
2
2x3
DIU Buffer
8 words x 64bits
rd_adr
12x3
rd_data
12x64
DIU interface
Buffer address generator
12x4
wr_adr
2x4
line_fin
nozzle_skew
max_nozzle_skew
4
line_dot_cnt
16
dwu_go_pulse
linesize
16
color_line_sense
2
color_base_adr
color_fifo_size
12x17
12x8
8
color_line_inc
color_enable
6
line_wr
buf_full
Configuration registers
max_write_ahead
8
filllevel
8
FIFO fill level
dwu_go_pulse
dwu_dnc_ready
dwu_ready
zero_fill
Dot Writer Unit
5
32
32
pcu_adr
pcu_dwu_sel
dwu_pcu_datain
dwu_pcu_rdy
pcu_dataout
pcu_rwn
dwu_llu_line_wr
llu_dwu_line_rd
PEP Controller Unit
LLU

FIG. 263


dwu_go_pulse
data_valid
max_nozzle_skew
4
line_size
16
Up count generator
Dot counter
Down count generator
line_fin
up_cnt
11
dn_cnt
11
color_line_sense[0]
color_line_sense[1]
Even bit-write decode
Odd bit-write decode
1
64
4
wr_en[0]
wr_bit[0][63:0]
wr_adr[0][3:0]
wr_en[1]
wr_bit[1][63:0]
wr_adr[1][3:0]
zero_fill
line_fin
line_dot_cnt
16
data_active
1
6
6
wr_dot_data
dot_data

FIG. 264


color_base_adr
12x17
color_line_inc
8
color_line_sense
2
Address generator
17
dwu_diu_wadr
dwu_go_pulse
line_wr
12
fifo_end
req_sel
4
last_wd
adr_update
Line count
Read Pointer
group_fin
3
color_cnt
buf_rd_en
req_update
req_active
Interface controller
12x8
color_fifo_size
dwu_go_pulse
2x4
wr_adr
2x3
rd_adr
buf_full
line_fin
6
color_enable
dwu_go_pulse
diu_dwu_wack
dwu_diu_wreq
dwu_diu_wvalid
64
64
dwu_diu_data
4
req_sel
12x64
rd_data
Buffer array
External
2x3
rd_adr

FIG. 265



Machine remains in same state by default
All outputs are zero unless otherwise stated

State Description:

Idle:	Idle state wait for active request
ColorSelect:	Select the color to update before requesting to DIU
Request:	Request issued wait for acknowledge
Data0:	Data word 0 transfer
Data1:	Data word 1 transfer
Data2:	Data word 2 transfer
Data3:	Data word 3 transfer

FIG. 266



FIG. 267



FIG. 268



M - Midway point in dots
N - Number of dots in a line

Note: Paper passing under printhead

FIG. 269


Generate dot order (to the PHI)
Odd Dot stream
13823,13821,13819,...
...,9749,9747,9745
9743,9741,9739,...
...,5,3,1
...,5,3,1
Even Dot stream
0,2,4,...
...,9738,9740,9742
9744,9746,9748,...
...,13818,13820,13822
6912 clock cycles
Transmit dot order (to the printhead)
Mid Point
Printhead Channel A
13823,13821,13819,...
...,9749,9747,9745
9744,9746,9748,...
...,13818,13820,13822
Printhead Channel B
0,2,4,...
...,9738,9740,9742
9743,9741,9739,...
...,5,3,1
4872 clock cycles
2040 clock cycles
9744 clock cycles
Even dots from Line Y
Odd dots from Line Y-5
Example: Line with 13824 dots, with 7:3 printhead

FIG. 270


NozzleSkew[Color 1]
printhead A
printhead B
vertical skew
non-printable area 1
printable area
non-printable area 2
LineSize
non-printable area 1 = inverted non-printable area 2

FIG. 271


DRAM
Color 0 Even
Color 0 Odd
Color 1 Even
Color 5 Even
Color 6 Odd
ColorBaseAdr[0]
ColorBaseAdr[1]
ColorBaseAdr[2]
ColorBaseAdr[3]
ColorBaseAdr[10]
ColorBaseAdr[11]
ColorBaseAdr[12]
DRAM
Dot Line 0
Dot Line 1
Dot Line 2
Dot Line N-2
Dot Line N-1
Dot Line N
ColorFifoSize = N lines

FIG. 272


Even dot generator
Odd dot generator
DIU Interface
DIU Buffer
8words x 64bits
x 6
FIFO Fill Level
Configuration registers
line_size
join_point[0]
phi_llu_ready[0]
llu_phi_avail[0]
llu_phi_data[0]
llu_go_pulse
join_point[1]
phi_llu_ready[1]
llu_phi_avail[1]
llu_phi_data[1]
rd_data
rd_adr
buf_emp[0]
buf_emp[1]
wr_data
wr_en
wr_adr
llu_en
line_rd
dwu_llu_line_wr
llu_dwu_line_rd
join_point
line_size
llu_go_pulse
fillevel
fifo_read_thres
current_ptr_a/b
color_base_adr
join_word
color_enable
color_rel_line
ptr_wr_en
ptr_wr_adr
ptr_wr_data
pcu_rwn
pcu_llu_sel
pcu_ad_adr
pcu_datout
llu_pcu_datain
llu_pcu_rdy
llu_diu_radr
diu_data
diu_llu_rvalid
diu_llu_rack
llu_diu_req

FIG. 273


buf_emp
llu_en
llu_go_pulse
phi_llu_ready
16
join_point
16
line_size
Dot count
dot_active
bit_sel
6
rd_adr
3
External Array
DIU buffers
x6
rd_data
6x64
data
6
6
6
1
1
dot_avail
dot_data

FIG. 274


Address generator
Word count
Color activate
Write pointers
Interface controller
color_end_adr
color_base_adr
llu_diu_radr
current_ptr_a
current_ptr_b
llu_go_pulse
join_word
join_point[1:0][7:0]
line_rd
color_enable
color_rel_line
llu_go_pulse
join_stall
ptr_sel
req_sel
odd_even_sel
adr_update
word_dec
color_start
wr_null
wr_data
diu_data
ptr_wr_data
ptr_wr_adr
ptr_wr_en
llu_go_pulse
wr_en
wr_adr
rd_adr
buf_emp
buf_wr_en
req_update
color_cnt
req_active
group_fin
llu_en
llu_go_pulse
llu_diu_rreq
diu_llu_rack
diu_llu_rvalid
color_enable

FIG. 275


Reset OR llu_go_pulse==1
Idle
req_update = 1
req_active==1 AND llu_en==1
color_cnt = 0
ColorSelect
color_enable[color_cnt]==0 &
color_cnt < 6
color_cnt++
color_cnt ==6
word_dec = 1
req_update = 1
group_fin = 1
color_enable[color_cnt]==0 AND
color_start[color_cnt]==1
AND color_cnt < 6
color_cnt ++
Request
llu_diu_rreq =1
diu_llu_rack==1
adr_update=1
Data0
write_en =1
wr_null = ~color_start[color_cnt]
diu_llu_dvalid==1 OR req_null==1
Data1
write_en =1
wr_null = ~color_start[color_cnt]
diu_llu_dvalid==1 OR req_null==1
Data2
write_en = 1
wr_null = ~color_start[color_cnt]
diu_llu_dvalid==1 OR req_null==1
Data3
write_en = 1
wr_null = ~color_start[color_cnt]
color_enable[color_cnt]==0 AND
color_start[color_cnt]==0 AND
color_cnt < 6
color_cnt ++
diu_llu_dvalid==1
OR req_null==1
Machine remains in same state by default
All outputs are zero unless otherwise stated
State Description:
Idle: Idle state wait for active request
ColorSelect: Select the color to update before requesting to DIU
Request: Request issued wait for acknowledge
Data0: Data word 0 transfer
Data1: Data word 1 transfer
Data2: Data word 2 transfer
Data3: Data word 3 transfer

FIG. 276


SoPEC
LLU
dot data
control
PHI
Temp data
control
CPU
dot data
test data, temperature
dot data
test data, temperature
Bi-lithic Printhead

FIG. 277


Without Rate equalization (7:3 head)
100 µsec
phi_lsyncl
phi_ph_data[0][1:0]
phi_ph_data[1][1:0]
phi_srclk[0]
phi_srclk[1]
With Rate equalization (7:3 head)
phi_lsyncl
phi_ph_data[0][1:0]
phi_ph_data[1][1:0]
phi_srclk[0]
phi_srclk[1]

FIG. 279



M - Midway point in dots
N - Number of dots in a line

Note: Paper passing under printhead

FIG. 280


Generate dot order (from the LLU)
Odd Dot stream
13823,13821,13819,..
...,9749,9747,9745
9743,9741,9739,...
...,5,3,1
Even Dot stream
0,2,4,...
...,9738,9740,9742
9744,9746,9748,...
...,13818,13820,13822
6912 clock cycles
Transmit dot order(to the printhead)
Mid Point
Printhead Channel A
13823,13821,13819,..
...,9749,9747,9745
9744,9746,9748,...
...,13818,13820,13822
Printhead Channel B
0,2,4,...
...,9738,9740,9742
9743,9741,9739,...
...,5,3,1
4872 clock cycles
2040 clock cycles
9744 clock cycles
Even dots from Line Y
Odd dots from Line Y-5
Example: Line with 13824 dots, with 7:3 printhead

FIG. 281


Generate dot order (from the LLU)
Odd Dot stream
9743,9741,9739...
...,5,3,1
Even Dot stream
0,2,4,...
...,9738,9740,9742
4872 clock cycles
Transmit dot order(to the printhead)
Mid Point
Printhead Channel A
9743,9741,9739...
...,5,3,1
0,2,4,...
...,9738,9740,9742
Printhead Channel B
4872 clock cycles
4872 clock cycles
9744 clock cycles
Even dots from Line Y
Odd dots from Line Y-5
Example: Line with 9744 dots, with 7:0 printhead

FIG. 282


PrintStart Edge
LsyncPre
LsyncPeriod
LsyncHigh
LsyncLow
phi_lsyncl
SrclkPre
SrclkPost
phi_srclk
phi_ph_data
FrclkPre
FrclkHigh
FrclkLow
phi_frclk

FIG. 283


Paper Direction
(200 dots)
Print area(4772 dots)
Type 0 Head IC (9744 dots)
Type 1 Head IC (4080 dots)
paper
Line Y-5
line Y


lsyncl
Case 1
LLU data
phi_ph_data
phi_srclk
Case 2
LLU data
phi_ph_data
phi_srclk
Case 3
LLU data
phi_ph_data
phi_srclk
100 dots
9544 dots
100 dots

FIG. 284


ICU
PEP Controller Unit
Line Loader Unit (LLU)
PrintHead Interface
phi_icu_linesync_int
phi_icu_print_rdy
phi_icu_page_finish
phi_icu_underrun
pcu_adrr
pcu_phi_sel
phi_pcu_datain
phi_pcu_rdy
pcu_dataout
pcu_rwn
phi_llu_ready
llu_phi_avail
llu_phi_data
Configuration Registers
Dot Counter
dot_cnt
6x32
dot_cnt_snap
cpi_io_wr
pin_config
Datapath Unit
data_config
fire_config
sync_config
data_st
data_fin
print_start
phi_go
page_len_line
PHI Controller
Fire Generator
fire_st
fire_rdy
Sync Generator
sync_en
last_line
line_st
line_fin
sync_err
debug_cntrl
debug_data_valid
lsyncl_o
lsyncl_i
frclk
srclk
ph_data
CPU IO Control
phi_lsyncl_i
phi_lsyncl_e
phi_lsyncl_o
phi_frclk_i
phi_frclk_e
phi_frclk_o
phi_readl
phi_ph_data_o
phi_srclk
Master SoPEC
Bi-lithic Printhead
pclk domain (160 Mhz)
doclk domain (320 Mhz)

FIG. 285


Machine remains in same state by default
All outputs are zero unless otherwise stated
State Description:
Reset: Normal reset state
SyncPre: Count the LsyncPre number of clock cycles
SyncLow: Count the LsyncLow number of clock cycles
SyncHigh: Count the LsyncHigh number of clock cycles
SyncWait: Wait for an input lsync pulse
SyncPeriod: Count the LsyncMinperiod number of clock cycles
Reset OR phi_go_pulse==1
Reset
lsyncl_o = 1
sync_en==1 AND phi_mode==slave
sync_en==0
sync_en==1 AND phi_mode==master
count = lsync_pre
SyncPre
lsyncl_o = 1
count!=0 count --
count==0 count = lsync_low
SyncLow
lsyncl_o = 0
count!=0 count --
count==0 AND last_line ==0 count = lsync_low line_fin = 1
count==0 count = lsync_high line_st = 1
SyncHigh
lsyncl_o = 1
count!=0 count --
count==0 AND last_line ==1
SyncWait
lsync_pulse_rise == 1 count = lsync_high line_st = 1
SyncPeriod
count!=0 count --
count==0 count = lsync_high
lsync_pulse_fall == 1 AND count!=0 sync_err =1
To Reset State

FIG. 286


lsync_pulse_rise
lsync_pulse_fall
Pulse Generator
output_en
1
en
Compare
8
cnt
8
lsync_i_delay
Counter Logic
8
synchonizer
1
1
1
lsync_i
lsync_deglitch_cnt

FIG. 287



Machine remains in same state by default
All outputs are zero unless otherwise stated

State Description:

Reset:	Normal reset state
FirePre:	Count the FrclkPre number of clock cycles, repeat count set to FrclkNum
FireHigh:	Count the FrclkHigh number of clock cycles
FireLow:	Count the FrclkLow number of clock cycles

FIG. 288


Reset OR phi_go_pulse==1
Reset
phi_go==1
data_st = 1
line_count =page_len_line
FirstLine
line_fin == 1 AND
data_fin !=1
data_fin==1
line_count --
Printstart
print_rdy =1
print_start ==1
phi_go_pulse==1
SyncWait
sync_en =1
data_fin == 1 AND
line_count != 1
line_count --
line_st == 1
data_st = 1
fire_st = 1
sync_st = 1
line_fin == 1 AND
data_fin !=1
LineTrans
Underrun
underrun_error =1
sync_en =1
data_fin == 1 AND
line_count == 1
line_count--
LastLine
last_line =1
sync_en =1
fire_rdy ==1
page_finish =1

FIG. 289


Line Loader Unit (LLU)
DataPath Unit
Dot Order B
Dot Order A
Dot Order Controller
Dot Buffer 32x6bits
Dot Buffer 32x6bits
Data Generator B
Data Generator A
Data serializer B
Data serializer A
print_head_size[1]
print_head_size[0]
dot_order_mode
data_st
print_head_rate[1]
print_head_rate[0]
dot_margin[1]
dot_margin[0]
phi_serial_order[1]
phi_serial_order[0]
line_st
phead_swap
mode_sel
dot_cnt_rst
mid_pt[1],line_fin[1]
mid_pt[0],line_fin[0]
gen_en[1]
gen_en[0]
ready[1]
ready[0]
dot_order_rdy
data_fin[1]
data_fin[0]
data_fin
srclk[0]
ph_data[0][1:0]
pclk domain (160 Mhz)
doclk domain (320 Mhz)

FIG. 290



Machine remains in same state by default
All outputs are zero unless otherwise stated

State Description:

Reset:	Normal reset state
Linestart:	Start processing first part of the line, wait for both mid_pt to be active
LineMid:	Switch over wait state allow pipeline to clear
LineEnd:	Line end processing wait for both line_fin to be active

FIG. 291


Machine remains in same state by default
All outputs are zero unless otherwise stated
State Description:
Reset: Normal reset state
SrclkPre: Count the SrclkPre number of clock cycles
DataGen1: Read Line Dot data from buffer
DataGen2: Read Line Dot data from buffer
DataGen3: Data gen wait state
Wait1: Data rate control wait state
Wait2: Data rate control wait state
Wait3: Data rate control wait state
MarginGen1:Generate DotMargin number of dots
MarginGen2:Generate DotMargin number of dots
MarginGen3:Generate margin wait state
SrclkPost: Wait for SrclkPost number of cycles
Reset OR phi_go_pulse==1
Reset
data_gen_fin =1
data_st==1
count = srclk_pre_load
SrclkPre
count==0
count --
count ==0
count = print_head_size
sr_init = 1
DataGen1
dot_active==1
count --
DataGen2
count --
rate_cnt --
DataGen3
count!=0 AND
dot_active
count==0 AND dot_margin !=0
count = dot_margin
count!=0 AND
dot_active==0
Wait3
dot_active==0
rate_cnt --
Wait2
Wait1
MarginGen1
MarginGen2
count --
MarginGen3
count!= 0
count --
count==0 AND
dot_margin == 0
count=srclk_post
sr_com = 1
count==0
count= srclk_post
sr_com = 1
SrclkPost
count!=0
count --

FIG. 292


pclk
doclk
dot_data[11:0]
Invalid
Valid[11:0]
Invalid
ph_data[1:0]
Invalid
1:0
3:2
5:4
7:6
9:8
11:10
Invalid
mux_sel
Invalid
0
1
2
3
4
5
gate_srclk
3.125ns
srclk
line setup edge
line complete edge

FIG. 293


ph_data[1:0]
2
2
dot_data[1:0]
dot_data[3:2]
dot_data[5:4]
dot_data[7:6]
dot_data[9:8]
dot_data[11:10]
mux_sel
3
Mux Logic
12
dot_data[11:0]
phi_serial_order
srclk
1
doclk
srclk_gen
1
Srclk Control Logic
gate_srclk
sr_init_edge
sr_com_edge
line_st_edge
Edge Detect
Edge Detect
Edge Detect
1
1
1
sr_init
sr_com
line_st
phead_swap
dot_data[11:0]
gate_srclk
sr_init
sr_com
dot_data[1:0][11:0]
gate_srclk[1:0]
sr_init[1:0]
sr_com[1:0]
Note: All registers are clocked on doclk

FIG. 294


V+
Color n
Type 0 printhead
Type 1 printhead
Type 2 printhead
Type 3 printhead
Type 4 printhead
Type 5 printhead
Type 6 printhead
Type 7 printhead

FIG. 295


Printhead A
V+
Printhead B
Color 5
Color 4
Color 3
Color 2
Color 1
Color 0
Gnd
Direction
of Paper Flow

FIG. 296



The printheads are facing downwards.
The ink is being shot down onto the page.

FIG. 297


printhead A
printhead B
non-printable area 1
printable area
non-printable area 2

FIG. 298


Type 0 Printhead
V+
Type 1 Printhead
Color 5
Color 4
Color 3
Color 2
Color 1
Color 0
0 2 4
1 3 5
m-6 m-4 m-2
m-5 m-3 m-1
m m+2 m+4
m+1 m+3 m+5
n-6 n-4 n-2
n-5 n-3 n-1
Gnd
The printheads are facing downwards.
The ink is being shot down onto the page.
Direction
of Paper Flow

FIG. 299



FIG. 300



FIG. 301



FIG. 302

The printheads are facing downwards.
The ink is being shot down onto the page.



FIG. 303



FIG. 304



FIG. 305



FIG. 306


Arrangement 1
Paper
Arrangement 2
Paper
Arrangement 3
Paper
Arrangement 4
Paper
Arrangement 5
Paper
Arrangement 6
Paper
Arrangement 7
Paper
Arrangement 8
Paper

FIG. 307


Pads
Nozzle Column
Nozzle Column
Nozzle Column
...
...
Nozzle Column
Nozzle Column
Nozzle Column
Fire/Select Shift Register
Dot SR 5/Colour 5
Dot SR 4/Colour 4
Dot SR 3Colour 3
Dot SR 2/Colour 2
Dot SR 1/Colour 1
Dot SR 0/Colour 0

FIG. 308


Column N
Fr
frclk
FrN
Fire Shift Register (forward path)
Fire Shift Register (reverse path)
Sel
SelClk
Select Shift Register
Dot Latch
Dot[5]
SrClk2
Dot Shift Register5
Pr
Dot Latch
CoreScan
Dot Shift Register5
Dot[4]
SrClk1
Dot Shift Register4
Dot[3]
SrClk0
Dot Shift Register4
Data[1]
Dot[2]
SrClk2
Dot Shift Register4
Dot[1]
SrClk1
Dot Shift Register4
Dot[0]
SrClk0
Dot Shift Register4
Data[0]

FIG. 309


Paper Movement
Ink shooting out of page towards reader
Reader looking through paper over print heads
V+
Gnd
A
A
n-2
n-1
m
m+1
0
1
Left Print Head - (n-m) nozzles
Right Print Head - m nozzles
paper
Y
X
Section A-A Through Even nozzles
paper
n-2
n-1
m
m+1
m-2
m-1
1 0
Left Print Head - (n-m) nozzles
Right Print Head - m nozzles

FIG. 310


Data[0]
Data[1]
SrClk
LSyncL
C0₀ C1₀ C2₀ C0₁ C1₁ C2₁ C0₂ C1₂ C2L
C3₀ C4₀ C5₀ C3₁ C4₁ C5₁ C3₂ C4₂ C5L

FIG. 311



a) Printing every n^{th} dot with all zero's in the fire select shift register



b) Printing every n^{th} dot with all one's in the fire select shift register



c) Printing every n^{th} dot with n zero's then n one's in the fire select shift registers

FIG. 312



FIG. 313



FIG. 314



FIG. 315



FIG. 316



FIG. 317


LsyncL
ReadL
Data$_A$[0]
Data$_B$[0]
SrClk
FrClk
Pr
b_A, Inen[13-0], count[0-13]$_A$
b_B, Inen[13-0], count[0-13]$_B$
L_A cycles
Fire Load Mode
Fire Initialise Mode

FIG. 318



FIG. 319


LsyncL
ReadL
Data[1]
SrClk
FrClk
Pr
Set up Test
Reset Nozzle Test Mode
Nozzle Test Output Mode
Set up Test

FIG. 320



FIG. 321


LsyncL
ReadL
Data
SrClk
FrClk
Pr
Set up Test
Dot Load Mode
CMOS Test Output Mode

FIG. 322



FIG. 323



FIG. 324



FIG. 325



FIG. 327


SoPEC boot rom
(includes boot0key public key)
validation via boot0key
dataset1: operating system
(includes ComCo public key)
validation via ComCo key
dataset2: operating parms
(includes OEM public key)
validation via OEM key
dataset4: OEM program code

FIG. 326



FIG. 328



FIG. 329



FIG. 330



FIG. 331



FIG. 332



FIG. 333



FIG. 334



FIG. 335



FIG. 336



FIG. 337



FIG. 338



FIG. 339



FIG. 340



FIG. 341



FIG. 342



FIG. 343



FIG. 344



FIG. 345



FIG. 346



FIG. 347



FIG. 348



FIG. 349



FIG. 350



FIG. 351



FIG. 352



FIG. 353



FIG. 354



FIG. 355



FIG. 356



FIG. 357



FIG. 358


Ink reservoir
QA Chip
Ink reservoir
QA Chip
Ink reservoir
QA Chip
Electrical connection to QA Chip
Electrical connection to QA Chip
Switch unit
Output Ink transfer mechanism
Ink output device
Ink output device
Ink output device
Ink refill unit
Ink cartridge interface unit
Ink cartridge
QA Chip
Electrical connection to QA Chip
Microprocessor assembly controlling refill process
User Interface

FIG. 359



FIG. 360



FIG. 361


Ink reservoir
QA Chip
Ink reservoir
QA Chip
Ink reservoir
QA Chip
Electrical connection to QA Chip
Electrical connection to QA Chip
Switch unit
Output Ink transfer mechanism
Ink output device
Ink output device
Ink output device
Ink refill unit
Multiple ink cartridge interface unit
Ink cartridge
QA Chip
Electrical connection to QA Chip
Ink transfer mechanism controls
Microprocessor assembly controlling refill process
User interface

FIG. 362



FIG. 363



FIG. 364



FIG. 365



FIG. 366



FIG. 367



FIG. 368



FIG. 369


bit 15
bit 0
0 0 0 0 MSelect 4 bits 0 0 0 0 0 RW Sense 3 bits
Word 0
bit 31
bit 16
0 0 0 0 0 0 0 0 KeyIdSelect 8 bits
bit 15
bit 0
bit 15 of ChipId
ChipId
bit 0 of ChipId
Word 1
bit 31
bit 16
bit 31 of ChipId
ChipId
bit 16 of ChipId
bit 15
bit 0
bit 47 of ChipId
ChipId
bit 32 of ChipId
Word 2
bit 15
bit 0
bit 63 of ChipId
ChipId
bit 48 of ChipId
bit 15
bit 0
WordSelect for first desiredM
Word 3
bit 31
bit 16
WordSelect for second desiredM (or pad 0s to nearest word if only one desired M)
bit 15
bit 0
WordSelect for third desiredM (if present)
Word 4
bit 31
bit 16
WordSelect for last desiredM (or pad 0s to nearest word if only three desired M)
bit 31
bit 0
Word 5
First word of first desiredM - corresponding to required MSelect and WordSelect for desiredM
bit 31
bit 0
Last word of last desiredM - corresponding to required MSelect and WordSelect for desiredM
bit 31
bit 0
First KeyId- corresponding to KeyIdSelect
bit 31
bit 0
Word 5+m
Last KeyId- corresponding to KeyIdSelect
bit 31
bit 0
R_L(LSW)
bit 31
bit 0
Word 5+m+5
R_L(MSW)
bit 31
bit 0
R_E(LSW)
bit 31
bit 0
Word 5+m+10
R_E(LSW)

FIG. 370


bit 31
bit 0
Word 1
Word 1 of Data
bit 31
bit 0
Word m
Word m of Data. m= Datalength.
bit 31
bit 0
R_E(LSW)
bit 31
bit 0
Word m+5
R_E(MSW)
bit 31
bit 0
R_L(LSW)
bit 31
bit 0
Word m+10
R_L(MSW)

FIG. 371


bit 31
bit 0
Word 1
Word 1 of Data
bit 31
bit 0
Word m
Word m of Data. m= Datalength.
bit 31
bit 0
R_{L2}(LSW)
bit 31
bit 0
Word m+5
R_{L2}(MSW)
bit 31
bit 0
R_{E2}(LSW)
bit 31
bit 0
Word m+10
R_{E2}(MSW)

FIG. 372


bit 15
bit 0
0 0 0 0 FieldSelect 4 bits 0 0 0 0 0 RW Sense 3 bits
Word 0
bit 31
bit 16
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
bit 15
bit 0
bit 15 of ChipId
ChipId
bit 0 of ChipId
Word 1
bit 31
bit 16
bit 31 of ChipId
ChipId
bit 16 of ChipId
bit 15
bit 0
bit 47 of ChipId
ChipId
bit 32 of ChipId
Word 2
bit 31
bit 16
bit 63 of ChipId
ChipId
bit 48 of ChipId
bit 31
bit 0
Word 3
MSW of lower field in FieldSelect
bit 31
bit 0
Word 3+m
LSW of lower field in FieldSelect
bit 31
bit 0
MSW of higher field in FieldSelect
bit 31
bit 0
Word 3+m+n
LSW of higher field in FieldSelect
bit 31
bit 0
R_E(LSW)
bit 31
bit 0
Word 3+m+n+5
R_E(MSW)
bit 31
bit 0
R_L(LSW)
bit 31
bit 0
Word 3+m+n+10
R_L(LSW)

FIG. 373


bit 15
bit 0
bit 15 of ChipId
ChipId
bit 0 of ChipId
Word 0
bit 31
bit 16
bit 31 of ChipId
ChipId
bit 16 of ChipId
bit 15
bit 0
bit 47 of ChipId
ChipId
bit 32 of ChipId
Word 1
bit 31
bit 16
bit 63 of ChipId
ChipId
bit 48 of ChipId
bit 31
bit 0
Word 2
KeyLock 1-bit
KeyId 30-bit
Variant Flag 1-bit
bit 31
bit 0
Word 3
R_E(LSW)
bit 31
bit 0
Word 8
R_E(MSW)
bit 31
bit 0
Word 9
EncryptedKey(LSW)
bit 31
bit 0
Word 13
EncryptedKey(LSW)

FIG. 374



FIG. 375



FIG. 376


bit 15
bit 0
bit 15 of ChipId
ChipId
bit 0 of ChipId
Word 0
bit 31
bit 16
bit 31 of ChipId
ChipId
bit 16 of ChipId
bit 15
bit 0
bit 47 of ChipId
ChipId
bit 32 of ChipId
Word 1
bit 31
bit 16
bit 63 of ChipId
ChipId
bit 48 of ChipId
bit 31
bit 0
Word 2
KeyLock 1-bit
KeyId 30-bit
Variant Flag 1-bit
bit 31
bit 0
Word 3
R_E(LSW)
bit 31
bit 0
Word 8
R_E(MSW)
bit 31
bit 0
Word 9
EncryptedKey(LSW)
bit 31
bit 0
Word 13
EncryptedKey(LSW)

FIG. 377


Transfer
Ink Refill QA Device
System
Ink QA Device
1- Read M_0 And M_1
2- Transfer Request
Read Output
Transfer Output
3- Write Transfer Output
Success or Failure
4- Read M_0 And M_1
5- StartRollBack
Read Outputs
6- Write Pre-rollback Output
Pre-rollback Output
Success or Failure
7- Read M_0 And M_1
8- RollBack
Read Output
Success or Failure
RollBack

FIG. 378


Read QA Device Being Upgraded
Call Transfer on the Upgrading QA Device
Write transfer output to QA Device Being Upgraded
Write successful
Yes
Read QA Device Being Upgraded
Upgrade Completed
Yes
No
Try applying transfer output again
Is repeat count > n
Transmission Problem likely Perform Rollback
Read QA Device Being Upgraded
Call StartRollBack on the Upgrading QA Device
Write pre-rollback output to QA Device Being Upgraded
Try applying pre-rollback output again
No
Write successful
Yes
Read QA Device Being Upgraded
Call RollBack on the Upgrading QA Device
RollBack Completed
Is repeat count > n
Transmission Problem likely Call StartRollBack again

FIG. 379


Refill Device QACo
Heirarchical Transfer
Heirarchical Transfer
Heirarchical Transfer
Refill Device ComCo#1
Refill Device ComCo#2
Refill Device ComCo#N
Heirarchical Transfer
Heirarchical Transfer
Refill Device OEM#1
Refill Device OEM#2
Refill Device OEM#N
Peer to Peer Transfer
Peer to Peer Transfer
Refill Device OEM#1 #1
Refill Device OEM#1 #2
Refill Device OEM#1 #N
Peer to Peer Transfer
Peer to Peer Transfer
Ink Device #1
Ink Device #2
Ink Device #N

FIG. 380


bit 15
bit 0
0 0 0 0 MSelect 4 bits 0 0 0 0 0 RW Sense 3 bits
Word 0
bit 31
bit 16
0 0 0 0 0 0 0 0 KeyIdSelect 8 bits
bit 15
bit 0
bit 15 of ChipId
ChipId
bit 0 of ChipId
Word 1
bit 31
bit 16
bit 31 of ChipId
ChipId
bit 16 of ChipId
bit 15
bit 0
bit 47 of ChipId
ChipId
bit 32 of ChipId
Word 2
bit 31
bit 16
bit 63 of ChipId
ChipId
bit 48 of ChipId
bit 15
bit 0
WordSelect for first desiredM
Word 3
bit 31
bit 16
WordSelect for second desiredM (or pad 0s to nearest word if only one desired M)
bit 15
bit 0
WordSelect for third desiredM (if present)
Word 4
bit 31
bit 16
WordSelect for last desiredM (or pad 0s to nearest word if only three desired M)
bit 31
bit 0
Word 5
First word of first desiredM - corresponding to required MSelect and WordSelect for desiredM
bit 31
bit 0
Last word of last desiredM - corresponding to required MSelect and WordSelect for desiredM
bit 31
bit 0
First KeyId- corresponding to KeyIdSelect
bit 31
bit 0
Word 5+m
Last KeyId- corresponding to KeyIdSelect
bit 31
bit 0
R_L(LSW)
bit 31
bit 0
Word 5+m+5
R_L(MSW)
bit 31
bit 0
R_E(LSW)
bit 31
bit 0
Word 5+m+10
R_E(LSW)

FIG. 381


Transfer
Parameter Upgrader QA Device
System
Printer QA Device
1- Read M_0 And M_1
Read Output
2- Transfer Request
Transfer Output
3- Write Transfer Output
Success or Failure
4- Read M_0 And M_1
Read Output
5- StartRollBack
Pre-rollback Output
6- Write Pre-rollback Output
Success or Failure
7- Read M_0 And M_1
Read Output
8- RollBack
Success or Failure
RollBack

FIG. 382


Read QA Device Being Upgraded
Call Transfer on the Upgrading QA Device
Write transfer outputs to QA Device Being Upgraded
Write successful
Yes
Read QA Device Being Upgraded
Upgrade Completed
No
Yes
Try applying transfer output again
Is repeat count > n
Transmission Problem likely Perform Rollback
Read QA Device Being Upgraded
Call StartRollBack on the Upgrading QA Device
Write pre-rollback outputs to QA Device Being Upgraded
Try applying pre-rollback output again
No
Write successful
Yes
Read QA Device Being Upgraded
Call RollBack on the Upgrading QA Device
RollBack Completed
Is repeat count > n
Transmission Problem likely Call StartRollBack again

FIG. 383



FIG. 384



FIG. 385


Translating device
C
1
4
System
2
External untrusted device
B
Trusted environment
3
5
System trusted device
A

FIG. 386



FIG. 387



FIG. 388


Central Processing Unit
IO Unit
Memory Interface Unit
Memory Components
Analogue Unit
Trim Unit
CPUInByteUsed
CPUOutByteWE
LocalIdWE
8 CPUIOData
InByteValid
OutByteValid
InByte
IOMode
MIUAvail
1 SDa
SClk
8
2
1
SysClk
CPUNewTrans
CPUGo
CPUAccessMode
CPUWriteMask
CPUAdr
CPUDataOut
MIUData
5 8 12 32 32
MIUAvail, MIURdy
2
1 FuseBlown
PMInByteUsed
PMOutByteWE
8 PMIOData
PwrFailing
MAURstOutL
FlashAdr
RAMAdr
WriteData
RAMRW
FlashCtrl
TMR
RAMOutEn
RAMData
FlashData
13 7 32 9 32 8
Trim
8
to all blocks
RstL
SysClk
VDD
GND

FIG. 389



FIG. 390



FIG. 391



FIG. 392


CPUNewTrans
CPUGo
newMemTrans
Go
Fetch Execute Unit
2
IOMode
OutByteValid
InByteValid
MIUAvail
MIURdy
Exec
Cmd
Cycle
Fetch
8
8 MIU8Data (msb)
32
MIUData
Program Counter Unit
PC 12
PCRamSel
1
CZ
pcSel
13 (15,11:0)
Address Generator Unit
AccessMode
5
CPUAccessMode
WriteMask
8
CPUWriteMask
EffAdr
12
CPUAdr
Acc
32
CPUDataOut
Cn
6
Z
32 Acc
Arithmetic Logic Unit
LocalIdWE
CPUOutByteWE
CPUInByteUsed
CPUIOData
ALUOutByteWE
ALUInByteUsed
ALUIOData
8
8
InByte

FIG. 393



FIG. 394



FIG. 395

Bit 7	Bit 6	Bit 5	Bit 4	Bit 3	Bit 2	Bit 1	Bit 0
PrilD6	PrilD5	PrilD4	PrilD3	PrilD2	PrilD1	PrilD0	R/*W 0 = write 1 = read

FIG. 396



FIG. 397


SClk pin
sclk0 (1 bit)
sclk1 (1 bit)
sclk2 (1 bit)
feSClkPrev (1 bit)
feSClkPrev
XOR
feSClk
reSClk
we
sclk3 (1 bit)
sclk4 (1 bit)
sclk5 (1 bit)
sclk6 (1 bit)
clear
SDa pin
sda0 (1 bit)
sda1 (1 bit)
sda2 (1 bit)
saturating counter (3 bits)
2 (msbs)
3
XOR
SDaRegSelect
SDaReg
we
sda3 (1 bit)
sda4 (1 bit)
sda5 (1 bit)
sda6 (1 bit)
sda7 (1 bit)
StartDetected (1 to 0)
StopDetected (0 to 1)

FIG. 398



FIG. 399



FIG. 400


ROR 1
ROR 3
ROR 24
ROR 31
ROR 8
32
XOR
1
RTMP (1 bit)
we
0
31 (msb)
MX3
rorOut
Exec
Logic1
18 (msb)
24 (msb)
6
8
MX1
MX2
Acc
1 (lsb)
6 (13-8)
8 (lsb)
InByte
Logic2
Cmd
Cn

FIG. 401


Cmd
Exec
8
1
Logic1
LocalIdWE
Acc
32
8 (lo bits)
8
ALUIOData
Logic2
ALUOutByteWE
Logic3
ALUInByteUsed

FIG. 402


+1
-1
VAL1
4+p
SP
(4 bits + p)
we
select
Fetch
PC
PCA
(12 × 12bits+p)
pcSel
Exec
12+p
VAL2
Logic3
Z
CZ
1 (bit4)
ADD
8
(hi bit = sign)
0x01
Logic4
MIU8Data
12 (lsb)
Acc
1(bit 15)
Acc
Cycle
Acc
becomes msb
Logic2
1 (bit6)
4 (lsb)
1 (bit0)
Cmd
Logic1
Logic0
PCRamSel
(1 bit)
PCRamSel

FIG. 403


PC
12
PCRamSel
1
001 | PCRamSel | 0
pcSel
nextEffAdr
nextAccessMode
pcSel
12
5
1
1
0
12
Adr
(12 bits + p)
12+p
VAL1
12
EffAdr
we
we
1
0
5
accessMode
(5 bits)
5
accessMode
Cycle
Fetch
Cn
6
Calculate Next
Address
6
Cn
Counter
Unit
CZ
6 Acc5-0
8
Acc7-0
2
AnSel
DataOut
9
bit7
1
Address Register
Unit
DataIn
9
8
0
1
8
MIU8Data
becomes
hi bit
we
WriteMask
(8 bits)
8
WriteMask
we
bit0
1
8
Logic1
Cmd
Logic2
1
Exec

FIG. 404



FIG. 405



FIG. 406


¬MRURdy
l adFus
(PROGRAM ∧ MRURdy ∧ ¬FuseBlown) ∨
(ACTIVE ∧ MRURdy ∧ ¬maskLoaded)
PROGRAM ∧
MRURdy ∧
MRUData ≠ FuseSig
ACTIVE ∧
MRURdy
PROGRAM ∧
MRURdy ∧
MRUData = FuseSig
MRURdy ∧
IdlePending_in
rstl
¬IDLE
wait4mode
ACTIVE ∧ MRURdy
∧ maskLoaded
IDLE
IDLE
idle
MRURdy ∧
¬IdlePending_in
MRURdy ∧
IdlePending_in
getMask
¬MRURdy
TRIM ∧
MRURdy ∧
¬FuseBlown
MRURdy ∧
IdlePending_in
¬TRIM
¬PROGRAM
erase
¬MRURdy
MRURdy ∧
¬IdlePending_in
MRURdy ∧
IdlePending_in
loadByte
¬InByteValid
InByteValid
¬MRURdy
writeByte
4096 states
¬lastOne ∧
MRURdy ∧
¬IdlePending_in
TRIM ∧
¬InByteValid
trim
4096 states
lastOne ∧ MRURdy ∧
¬IdlePending_in
InByteValid

FIG. 407


MRUData
32
PMEn
CPUNewTrans
CPUAccessMode
5
CPUAdr
12
CPUDataOut
32
CPUWriteMask
8
PMNewTrans
PMRW
1
PMEraseDevice
1
PM32Out
32
MRURdy
Arbitration Logic
NewTrans
6 AccessMode
12 Adr
32 ReqDataOut
8 WriteMask
Memory Request Logic
1 MRUTestWE
MRURAMSel
32 RAMData
MAURdy
32 MRUDataOut
3 MRUMode
13 MRUAdr
MRUNewTrans
8 FlashData
2 IOMode

FIG. 408



FIG. 409



FIG. 410



FIG. 411



FIG. 412



FIG. 413